

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 200520

PRIMARY CORNER DESCRIPTION S 1/16 S 7 | S 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Weyco C.S. 53/112-7
In 1957, Vernon W. Hosford, for Weyerhaeuser Timber Co., set
a 1½" x 36" Iron pipe, proj. 6" above the ground.
30" Hemlock N.52°E 30.2 ft.
30" Cedar N.73°W. 30.6 ft.

Glen McChensey for Weyerhaeuser Timber Co - 7/29/1959 - CS 53/112-7

Found - 1½" Iron pipe
30" Hemlock N.52°E 30.2 ft. scribed.
30" Cedar N.73°W. 30.6 ft. scribed added "W" nail
& plat.
New - 58" Fir S.10°E 22.6 ft. "W" nail & plat.
Notes - Ground cover is Salal and fern.
Slope face is N.35°E. on minus 50%
Old growth to the East. To the West to be logged 1959

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor
Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO
records Vol. 57 Page(s) 22797-98

The S 1/16 sec. cor. of secs. 7 & 8, established by Hosford,
in 1957, and is accepted as the cor., monumented with an iron
pipe, 1½" dia., firmly set, projecting 6" above the ground,
from which the remains a bearing tree mkd. by Hosford
A sawed, decayed cedar stump, 33" dia., bears S.84°W.,
19.0 ft. dist., with a healed blaze and a "W" nail in
lower chaining notch.
and bearing trees of unknown origin
A hemlock, 11" dia., bears S.62½°W., 21.5 ft., with
fragmentary scribe marks visible on a partially healed
blaze.
A hemlock, 10" dia., bears N.7°W., 17.8 ft., with
fragmentary scribe marks visible on a partially healed
blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 25" in the
ground, directly over the iron pipe, with brass cap mkd.
S 1/16
S7|S8
2010
Deposit a magnet in a white plastic case at the base of the
stainless steel post.

continued next page

1

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 200520

PRIMARY CORNER DESCRIPTION S 1/16 S 7 | S 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 1/28/2026 - C.S. File 67/62-08

Found - 3/4" BLM brass cap proj. 3" steep post on South edge.
Sawn - burned 32" x 6 ft. cedar stump S.83°W. 20.1 ft. (Rec. S84.°W. 19.0 ft.) "W" nail off center of face. Bears S.86°W. 18.8 ft. face mostly burned off low. Axe marks remain.

Fallen - burned 14" hemlock, no measurable position remains partly healed single blaze. No scribes visible

Burned, broken off, shattered 10" x 3 ft. hemlock stump N.7°W. 17.8 ft. Face burned off.

New - Burned - sawn 18"x ft. hemlock stump. S.66°E. 14.2 ft. 3/2" mag nail top center over root crown.

Notes - Mon is approx. 450 ft. East of gravel road.
Area burnt 9/2020

Mon on moderately steep N.N.E. slope in strip of burnt forest running N.W. rest of area large clearcut.

Compass decl. 14 1/4° E.
TRIMBLE GEO XT POSITION
43.40616920° N.
122.97262521° W.