

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, T26-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 9 Page(s) 3583)

-----  
Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 5, 6, 31 and 32, mkd. T25S S32 on NE.; R2W S5 on SE.; R26S S6 on SW.; and S31 on NW. faces, with 5 notches on E. and 1 notch on W. edges, from which  
A Maple 6" dia., bears N.50°E., 66 lks. dist. mkd. T25S R2W S32 BT.  
A Fir 10" dia., bears S.5°E., 65 lks. dist. mkd. T26S R2W S5 BT.  
A Fir 6" dia., bears S.85°W., 55 lks. dist. mkd. T26S R2W S6 BT.  
A Cedar 8" dia., bears N.50°W., 57 lks. dist. mkd. T25S R2W S31 BT.

GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4275 and 4276-77)

-----  
(Page 4275)  
Search for cor. of secs. 5 & 6, but find no trace. Set temp. cor. of secs. 5 and 6.  
(Pages 4276-77)  
Apportioned distance.  
A Fir tree, 8" dia. for cor. of secs. 5 and 6, mkd. T26S S5 on SE.; and R2W S6 on SW. face, with 5 notches on E. and 1 notch on W. side; from which  
A Fir 5" dia., bears S.40°E., 10 lks. dist. mkd. T26S R2W S5 BT.  
A Fir 10" dia., bears S.50°W., 32 lks. dist. mkd. T26S R2W S6 BT.

BLM Resurvey by Irving Zirpel & Wm. Glenn Under Group #404, Surveyed May/Oct. 1959 - (DCSO records Vol. 30 Page(s) 12721-22)

-----  
The cor. of 5 & 6 only, reestablished by Collier in 1913, monumented by a Fir, 13" dia., with a healed blaze and 1 notch on the W., and a healed blaze and 5 notches on the E. side, from which the 1913 bearing trees;  
A down and rotted Fir, 6" dia., bears S.40°E., 10 lks. dist., with scribe marks S5 BT visible on an opened and rotted blaze.  
A down and rotted Fir 15" dia., bears S.50°W., 32 lks. dist., with scribe marks T26S R visible on an opened and rotted blaze.  
(Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 208100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, T26-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

and locally established bearing trees:  
A Fir 13" dia., bears S.75°W., 53 lks. dist. with an  
opened blaze, no scribe marks visible.  
A Fir 15" dia., bears N.14½°W., 13 lks. dist. with a  
healed blaze.  
Add two new bearing trees:  
A Fir 24" dia., bears S.68°E., 75 lks. dist. mkd. T26S R2W  
S5 BT.  
A Fir 14" dia., bears S.30°W., 36 lks. dist. mkd. T26S R2W  
S5 BT.

Douglas Co. Surveyors Office - John Powell and E. Monrean,  
crew - July 3, 1972 - C.S. File 54/40-200

-----  
Found - Corner tree, broken stob.  
24" D.Fir, now down, S.68°E., 49.5 ft., shows good  
scar.  
14" D.Fir, now down, S.30°W., 23.8 ft.

Set Brass cap on side of Corner tree (14"), cap mkd.

County Surveyors Office

T 25 S R 2 W

S 32

S 6 | S 5

T 26 S

1972

New BTs- 17" D.Fir N.14½°W., 8.6 ft. scribed T25S R2W S32 CS  
BT.

15" D.Fir S.75°W., 35.0 ft. scribed T26S R2W S6 CS  
BT.

No trees too good to the SW. because of rock bluff directly  
South of corner, approx. 15 ft. high.

Fd. Corner OK, and used in BLM Resurvey by Daniel Berry;  
Harvey Wofford; G. Steven Popken, Cadastral Surveyors, under  
Group #'s 786, 848 and 854. And Glenn S. Baughman, L.S. #536,  
under Contract #52500-CT5-1116, Surveyed July 1972/Oct. 1975  
- (DCSO records Vol. 36 Page(s) 15106-07)