

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 32

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

V.W. Hosford - For: Evans Products Co. - Feb./Oct. 1960 - C.S. File 51/144 - M19-77  
-----  
Drove a 1½" iron pipe 36" long, 12" above the ground, from which:  
20" Fir bears S.83½°E., 25.0 ft. mkd: C ¼ S32 253 BT.  
14" Hemlock bears N.57°W., 5.4 ft. mkd: C ¼ S32 253 BT.

BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford, & G. Steven Popken Cadastral Surveyors & Glenn S. Baughman, LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct. 1975 - (DCS0 recs Vol. 36 Page 15132)  
-----  
The center ¼ sec. cor. of sec. 32, established & recorded by Hosford, in 1960, monumented with an iron pipe, 1½" dia., firmly set, protruding 5" above ground, from which the remains of the bearing trees mkd. by Hosford:  
A root hole, bears S.74°E., 33 lks., with a down hemlock alongside, 20" dia., with healed blaze.  
A hemlock snag, 17" dia., bears N.58°W., 9 lks., with scribe marks C¼ S32 visible on open blaze.  
At the corner point  
Set an iron post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd.  
C ¼  
S 32  
1975  
from which new bearing trees  
A cedar, 27" dia., bears S.42°E., 61½ lks., mkd. C¼ S32 BT  
A cedar, 14" dia., bears N.65°W., 18½ lks., mkd. C¼ S32 BT  
Reset iron pipe alongside iron post.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 5/4/2022 (Filed 7/20/2022) - C.S. File 67/52-38  
-----  
Found - 3¾" BLM brass cap (properly mkd) on 2" I.D. iron pipe proj. 14". IP NNW 0.3 ft proj. 8".  
OBT - Root hole N.58°W., 5.94 ft.  
BLM BTS-  
Burned hollow 20"x5 ft Cedar stump s.43½°E., 40.6 ft. (rec. S.42°E.)  
Burned hollow 14"x3½ ft. Cedar stump N.67½°W., 12.2 ft. (Rec. N.65°W.,)  
New - Burnt-dead 15" Hemlock S.39°W., 9.8 ft. No blaze or scribe. 3" PK right side center.  
5/8"x30" Iron rod N.9°W., 30.6 ft., painted red, proj. 8"  
Note - Area burnt 9/2020.  
Continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 240140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Corner is approx. 50' south of beginning of landing  
at end of logging road.  
Compass decl. 14½°E.  
See attached sketch  
Lat: 43°21'04.85"N Long: 122°57'47.10"W