

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3639)

Set basalt stone 18x9x8", 12" in the ground for ¼ sec. cor. marked ¼ on N face, from which

A fir, 16" dia., bears N.15°W., 118 lks., mkd: ¼ S29 BT.

A fir, 20" dia., bears S.53°E., 11 lks., mkd: ¼ S32 BT.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13236-7)

The ¼ sec. cor. of secs. 29 & 32, monumented with a basalt stone, 18x9x8" firmly set 12", in the ground, marked ¼ on the N face, from which the original bearing trees:

A fir, 34" dia., bears N.18°W., 112 lks. with a healed blaze. (Rec bearing & dist., N.15°W., 118 lks.)

A fir, 32" dia., bears S.43°E., 12 lks., with a healed blaze. (Rec bearing & distance, S.53°E., 11 lks.)

At the corner point

Set an iron post, 28" long, 2½" dia., 25" in the ground & in a mound of stone, 2 ft. base, to top, with brass cap mkd:

¼ $\frac{S\ 29}{S\ 32}$

T25S R2W

1962

Deposit the original corner stone alongside the iron post.

Fd. & used on BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford, & G. Steven Popken Cadastral Surveyors & Glenn S. Baughman, LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15127)

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor & Robert Browning, Surveying Technician, under Group #1659, surveyed June/July 1993 - (DCSO recs Vol. 51 Pages 19417-8)

The ¼ sec. cor. of secs. 29 & 32, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.

from which the original bearing trees

A fir, 35" dia., bears S.43°E., 12 lks., with healed blaze

A fir, 37" dia., bears N.18°W., 112 lks. with healed blaze