



PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Top of apparent orig, basalt corner stone protrudes 2" above ground lies along NW edge of I.P. stone, is firmly set. Did not disturb to look for marks. Orig. BT, a 14" now 19" dia. 4 ft. high shattered rotted D.Fir stump with fragmentary scribing "20" bears N.25°E., 45.0 ft. (Agrees well with orig. brg. dist. 44.2 ft. is a face measurement: Orig. BT a 6" now 19" dia. dead 50 ft. high D.Fir snag with a fully healed single blaze bears S.51½°E., 35.6 ft. (Rec. S.48°E. orig. & S.50°E., per 1962 resurvey, dist. agrees well with rec) 1962 BT, a 5" now 9" dia. dead D.Fir with a fully healed single blaze bears N.49½°W., 13.2 ft. (agrees with record).

New BTs- 5" D.Fir double blazed & scribed "¼ S29 CS BT" bears S.25°W., 28.9 ft.  
8" D.Fir double blazed & scribed "¼ S29 CS BT" bears S.86°W., 22.7 ft.  
5" D.Fir double blazed & scribed "¼ S20 CS BT" bears N.18½°E., 23.7 ft.  
8" chinquapin double blazed & scribed "¼ S20 CS BT" bears N.75°E., 28.9 ft.

Corner lies near top of a rock bluff.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor & Robert Browning, Surveying Technician, under Group #1659, surveyed June/July 1993 - (DCSO records Vol. 51 Page 19422)

-----

The ¼ sec. cor. of secs. 20 & 29, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

- A fir stump, 18" dia., bears N.27°E., 67 lks., with scribe marks S BT visible on decayed blaze.
- A fir snag, 18" dia bears S.50°E. 54 lks with healed blaze and the remains of a bearing tree mkd. by Brooks
- A fir stump, 11" dia., bears N.49½°W., 20 lks., with decayed snag lying alongside, with healed blaze. and bearing trees mkd. by Smith & Flause, in 1986
- A fir, 7" dia., bears N.18°E., 35 lks., with healed blaze.
- A chinquapin, 8" dia., bears N.75°E., 43 lks., with scribe marks ¼ S20 CS BT visible on open blaze.
- A fir, 7" dia., bears S.25°W., 44 lks., with healed double blaze.
- A fir, 11" dia., bears S.85°W., 33 lks., with healed double blaze.

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 3/15/2023 - C.S. File 67/55-61

-----  
Found - 3/4" BLM brass cap (properly mkd) up 5".  
Sawn, burned, 15"x1 ft. Fir stump N.18°E., 23.1 ft.,  
face inside evident, add 3/2" mag nail top center.  
New - 5/8"x30" I.Rod with DCS0 plastic cap, N.53 1/2°E., 11.7  
ft., up 4".  
5/8"x30" I.Rod with DCS0 plastic cap, S.89 1/2°W., 14.5  
ft., up 4".  
5/8"x30" I.Rod with DCS0 plastic cap, N.21°W., 10.2  
ft., up 4".  
Note - Gentle South slope running to steep South slope,  
large clear-cut to north, tree line to south.  
Area burnt 9/2020  
Compass decl. 14 1/2°E.

Lat: 43°22'23.49"N Long: 122°37'41.59"W  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 196994.917 E 262899.879 OCRS added 8/21/2024