

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3651)

Set a cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ on N & S17 on S faces, from which
 A hemlock, 8" dia., bears S.6°W., 20 lks., mkd: ¼ S17 BT.
 A fir, 5" dia., bears N.35°W., 21 lks., mkd: ¼ S8 BT.

V.W. Hosford - For: Evans Products Co. - Nov. 10, 1958 - C.S. File 42/398

No trace of the orig. corner post or BT. in. sec 8
 8" Hemlock, which from corner bears S.6°W., 20 lks. is orig. still standing & now 16" dia. From this tree the position of the corner was determined & at this point I drove a 1½" iron pipe 36" long, 24" in ground & marked new BT:
 A Hemlock 15" dia. bears N.75°W. 29.9 ft. mkd. ¼ S8 253 BT
 Beside the IP, I set a 4" cedar post mkd. ¼ S8 & 7 253.

Glen McChesney, WEYCO - 3/24/1959 - C.S. File 53/112-8

FD. GLO SW BT & Hosford's IP & 2 BTs.
 Added "W" nail & plate to GLO SW BT & Hosford's NW BT.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13241)

The ¼ sec. cor. of secs. 8 & 17, perpetuated & recorded by V W Hosford in 1957, monumented with an iron pipe, 36", long, 1½" dia., firmly set 30" in the ground, from which the only remaining original bearing tree:

A hemlock, 17" dia., bears S.6°W., 20 lks., with scribe mark 4 visible on opened blaze.
 and a tree marked by Hosford in 1957
 A hemlock, 18" dia., bears N.72½°W., 46½ lks., with scribe marks ¼ S8 253 BT visible on unhealed blaze.

At the corner point

Set an iron post, 28" long, 21" dia., 26" in the ground, with brass cap marked

¼ $\frac{S \ 8}{S \ 17}$
 T25S R2W
 1962

from which new bearing trees

A hemlock 18" dia., bears N.21°W., 38 lks., mkd ¼ S8 BT.
 A hemlock 14" dia., bears S.1½°W., 46 lks., mkd ¼ S17 BT.
 Reset the iron pipe alongside the iron post.

cont.

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Harvey Christensen - 1/1999 - C.S. File 65/23-11

-
- Found - 3¼" dia., BLM brass cap on 1½" iron pipe, protruding 3" above ground level.
18" Hemlock stump, S.6°W., 12.9 ft. to ctr. with visible scribing.
19" Hemlock stump N.17°W., 24.9 ft., to ctr. with visible scribing
1½" dia., IP protruding 1.0 ft. above ground. Set firmly in place, next to found corner brass cap monument.
- New - 5" D.Fir N.40°E., 11.8 ft. to ctr. Blazed at breast high & scribed "X" and low blaze scribed "BT"
5" D.Fir S.52°E., 40.0 ft. to ctr. Blazed at breast high & scribed "X" and low blaze scribed "BT"
5" D.Fir N.84°W., 28.1 ft. to ctr. Blaze & scribed at breast high "X" & low blazed & scribed "BT"
5" D.Fir S.78°W., 32.2 ft. to ctr. Blazed & scribe at breast high "X" & low blaze and scribed "BT"
Steel post West 1.0 ft.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22794-5

The ¼ sec. cor. of secs. 8 & 17, perpetuated by Christensen, in 1999, monumented with an iron post, 2½" dia., firmly set, projecting 8" above the ground, (alongside of which is an iron pipe, 2" dia., firmly set, projecting 15 ins. above the ground), with brass cap (properly) mkd.

from which the remains of an original bearing tree

A decayed hemlock stump, size indeterminate, bears S.6°W., 13.2 ft., with no marks visible.

and the remains of a bearing tree mkd. by Brooks

A decayed hemlock stump, size indeterminate, bears N.21°W., 25.1 ft., with scribe marks ¼ S8 visible on a partially healed blaze.

and bearing trees mkd. by Christensen

A fir, 8" dia., bears N.34¼°E., 11.6 ft., with a healed double blaze.

A fir, 11" dia., bears S.60½°E., 39.9 ft., with a healed double blaze.

A fir, 9" dia., bears S.70¼°W., 31.1 ft., with a healed double blaze.

A fir, 10" dia., bears N.86¾°W., 27.9 ft., with a healed double blaze.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias	Description

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2348, Surveyed Aug. 2011 - (DCSO records BLM Plat T25-2W 2012-1 & Vol. 58 Pages 22940-1)

The ¼ sec. cor. of secs. 8 & 17, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, (alongside of which is an iron pipe, 2" dia., firmly set, projecting 15" above ground), with brass cap (properly) mkd. from which the remains of an original bearing tree

A decayed hemlock stump, size indeterminate, bears S.6°W., 13.2 ft., no marks visible and a spike driven in the base, oriented towards the cor., with a W stamped in the head.

and the remains of a bearing tree mkd. by Brooks

A decayed hemlock stump, size indeterminate, bears N.21°W., 25.1 ft., with scribe marks ¼ S8 visible on partially healed blaze.

and BTs mkd. by Christensen, in 1999

A fir, 8" dia., bears N.34¼°E., 11.6 ft., with a healed double blaze.

A fir, 11" dia., bears S.60½°E., 39.9 ft., with a healed double blaze.

A fir, 9" dia., bears S.70¼°W., 31.1 ft., with a healed double blaze.

A fir, 11" dia., bears N.86¾°W., 27.9 ft., with a healed double blaze.

A search was made for all original line trees bet. secs. 8 and 17 and none were recovered.