

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 9 Page(s) 3583)

-----  
Set Cedar post 3" sq., 3 ft. long, 24" in the ground for ¼ sec. corner mkd. ¼ S on N. face, from which  
A Cedar 5" dia., bears N.45°E., 7 lks. dist. mkd. ¼ S BT.  
A Cedar 6" dia., bears S.30°W., 12 lks. dist. mkd. ¼ S BT.

GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4275 and Page 4277)

-----  
(Page 4275)  
Search for ¼ sec. cor., could find no trace. Set temp. ¼ sec.cor.  
(Page 4277)  
Apportioned distance.  
Set a basalt stone 20x8x4 ins., 15" in the ground, for ¼ sec. cor. of sec. 5, marked ¼ on S. face; from which  
A Chinquapin 6" dia., bears S.42°E., 25 lks. dist. mkd. ¼ S5 BT.  
A Fir 30" dia., bears S.43°W., 96 lks. dist. mkd. ¼ S5 BT.

BLM Resurvey by Irving Zirpel & Wm. Glenn Under Group #404, Surveyed May/Oct. 1959 - (DCSO records Vol. 30 Page(s) 12721)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd:

-----  
T 26 S R 2 W  
¼ S 5  
1959

from which  
A Fir 15" dia., bears S.50°E., 26 lks. dist. mkd. ¼ S5 BT.  
A Fir 10" dia., bears S.68½°W., 29 lks. dist. mkd. ¼ S5 BT.

Cor. Fd. OK and used in BLM Resurvey by Daniel Berry; Harvey Wofford; G. Steven Popken, Cadastral Surveyors, under Group #'s 786, 848 and 854. And Glenn S. Baughman, L.S. #536, under Contract #52500-CT5-1116, Surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15105)