

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 260260

PRIMARY CORNER DESCRIPTION NE 1/16 Sec 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor & Robert Browning, Surveying Technician, under Group #1659, surveyed June/July 1993 - (DCSO records Vol. 51 Page 19426-7)

Point for the NE 1/16 sec. cor. of sec. 29, at intersection with the E. and W. centerline of the NE¼.
Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd. NE 1/16 S 29
1993
from which
 A fir, 10" dia., bears N.53°E., 26 lks., mkd. X BT.
 A fir, 14" dia. bears N.78°W., 17 lks. mkd. NE 1/16 S29 BT
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 4/1/2024 - C.S. File 67/57-46

Found - 3¼" BLM brass cap (properly mkd) on 2" I.D. iron pipe up 2"
 Burned, dead 14" D.Fir N.53°E., 19.0 ft. (rec. 26 lks 17.2 ft) fully healed double blaze, add 3½" mag nail right side center.
 Burned, sawn 20"x6' D.Fir stump N.78°W., 11.5 ft. fully healed single blaze, add 3½" mag nail right side center.
Note - Mon. on steep NW slope burned forest NE'ly, rest is clear cut.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 195624.524 E 263887.550