

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3627-8)

-----  
The point for see. cor. falls on a basalt stone in place 3x2x1½ ft. above ground. At the exact cor, point I mark a cross (x) with 1 notch on S & 4 notches on E edges of stone, from which -

- A pine, 4" dia. bears N.31°E., 28 lks. mkd T25S R2W S28 BT
- A maple, 4" dia. bears S.15°E. 27 lks. mkd T25S R2W S33 BT
- A fir, 48" dia. bears S.25°W., 30 lks. mkd T25S R2W S32 BT
- An elder, 5" dia. bears N.11°W. 8 lks. mkd T25S R2W S29 BT

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13229-30)

-----  
The cor. of secs. 28, 29, 32 & 33 monumented with a shattered basalt stone, 3x2x1½ ft., above ground, marked with an X on top, & 1 notch on the S & 3 notches on the E edge, from which the original bearing trees

- A down & rotted pine, 12" dia., bears N.31°E., 28 lks., with no marks remaining.
- A maple, 9" dia., bears S.11°E., 27 lks., with a healed blaze. (Record bearing, S.15°E.)
- A fir, 65" dia., bears S.29°W., 32 lks., with no marks visible on partly opened blaze. (Rec. bearing & dist., S.25°W., 30 lks.)

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

T25S	R2W
<u>S 29</u>	<u>S 28</u>
S 32	S 33
1962	

from which a new bearing tree and a bearing object

- The W. face of a rock outcrop, bears N.80°E., 3½ lks., marked X BC.
- A hemlock, 20" dia., bears N.21°W., 38½ lks., marked T25S R2W S29 BT.

Deposit the original corner stone around the iron post, in the form on a mound, 3 ft. base, to top.

Glen McChesney, WEYCO - 12/16/1969 - C.S. File 53/112-43

-----  
 Found - 1962 Brass cap  
           48" Fir S.25°W., 18.0 ft. (Orig)  
           22" Hemlock N.19½°W., 25.0 ft. 1962  
 continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>New - Added "W" nail &amp; plate to 2 fd. BTs. 14" Madrone stump, S.16°E., 59.2 ft., "W" nail &amp; plate. 12" Fir N.8°E., 26.9 ft. "W" nail &amp; plate.</p>
<p>Fd. &amp; used on BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford, &amp; G. Steven Popken Cadastral Surveyors &amp; Glenn S. Baughman, LS, under contract #52500-CT5-1116 &amp; Group E 786, 848, &amp; 854, surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15124)</p>
<p>BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23339)</p> <p>-----</p> <p>The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2½" dia., firmly set, in a mound of stone, 3 ft. dia. base, to top, with a brass cap (properly) mkd. from which the remains of an original bearing tree</p> <p>A D.Fir, 62" dia., bears S.29°W., 21.1 ft., with a healed blaze.</p> <p>and new bearing trees</p> <p>A yew, 10" dia., bears N.11°E., 28.0 ft., mkd. T25S R2W S28 BT.</p> <p>A D.Fir, 10" dia., bears S.40½°E., 32.8 ft., mkd. T25S R2W S33 BT.</p> <p>A R.Cedar, 17" dia., bears N.33½°W., 18.3 ft., mkd. T25S R2W S29 BT.</p> <p>The NE. rock outcrop bearing object, mkd. by Brooks in 1962, was searched for but not recovered.</p>
<p style="text-align: right;">2</p>