

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3629-30)

-----  
Set basalt stone 22x10x8", 17" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A hemlock, 12" dia., bears N.41°E., 31 lks., mkd: ¼ S28 BT

A fir, 20" dia., bears S.81°W., 59 lks., mkd: ¼ S29 BT.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13230-1)

-----  
The ¼ sec. cor. of secs. 28 & 29, monumented with a basalt stone, 22x10x8", loosely set 6" in the ground, marked ¼ on the W face, from which the original bearing trees:

A hemlock, 26" dia., bears N.39°E., 31 lks., with a healed blaze. (Record bearing, N.41°E.)

A rotted fir snag, 18" dia., bears S.84°W., 59 lks., with fragmentary scribe marks visible on opened blaze. (Record bearing, S.81°W.)

At the corner point

Set an iron post, 28" long, 2½" dia., 27" in the ground with brass cap marked

¼  
S 29 | S 28  
T25S R2W  
1962

from which a new bearing tree and a bearing object

The W. face of a rock outcrop, under overhang, bears S.70¼°E., 36½ lks., marked X BO.

A cedar, 10" dia., bears N.68½°W., 42½ lks., mkd ¼ S29 BT  
Deposit the original corner stone alongside the iron post.

Glen McChesney, WEYCO - 12/30/1969 - C.S. File 53/112-44

Found - 1962 brass cap.

26" hemlock stump N.39°E., 19.9 ft. to face. (Orig.)  
ADDED "W" NAIL & PLATE.

20" fir snag, scribing visible, S.84°W., 38.9 ft. to face. (Orig.)

"X" on rock outcrop bears S.71°E., 25.1 ft. 1962

10" cedar N.67°W., 28.8 ft., scribing visible. 1962

New - 60" Fir S.19°W., 9.6 ft., with "W" nail & plate.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias	Description

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor & Robert Browning, Surveying Technician, under Group #1659, surveyed June/July 1993 - (DCSO records Vol. 51 Page 19416)

The ¼ sec. cor. of secs. 28 & 29, monumented with an iron post, 2½" dia., firmly set flush with the ground, with original basalt stone alongside with brass cap (properly) mkd from which the remains of the original bearing trees

A sawed hemlock stump, 24" dia., bears N.39°E., 31 lks., with healed blaze.

A decayed fir snag, 18" dia., bears S.84°W., 59 lks., no marks visible.

and the bearing object and remains of a BT mkd. by Brooks

The west face of a rock outcrop with overhang, bears S.70¼°E., 36½ lks. dist., mkd. BXO.

A sawed cedar stump, 15" dia., bears N.68½°W., 42½ lks., with healed blaze.

and a new bearing tree

A hemlock, 6" dia., bears N.21°W., 100 lks. mkd. ¼ S29 BT.

Ken Hoffine - For: Lone Rock Timber Co - Jan. 2020 - C.S. File 65/105-12

Found - 1962 BLM brass cap marked ¼ S29|S28 T25S R2W  
56" D.Fir stump bears S.23°W., 9.0' to face (record S.19°W., 9.6') tag and healed face.

20" D.Fir bears N.71¼°W., 16.1' we scribe ¼ S29 BT and tag.

18" D.Fir bears N.36¼°E., 29.7' we scribe ¼ S28 BT and tag.

"X" on rock face bears S.76°E., 21.9' (record S.70¼°E., 24.09' (36.5 lks)).

Note - Brass cap lies on steep rocky NW slope at ground level.

We place 5½ foot steel U-Post beside.