

PRIMARY CORNER DESCRIPTION Cor. Secs 16, 17, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3632)

Set a basalt stone 16x10x8", 11" in the ground for cor. for cor. of secs. 16, 17, 20, & 21 marked with 3 notches on S & 4 notches E edges, from which

A hemlock, 6" dia., bears N.54°E., 35 lks., mkd: T25S R2W S16 BT.

A hemlock, 10" dia., bears S.44°E., 26 lks., mkd: T25S R2W S21 BT.

A fir, 7" dia. bears S.13°W., 32 lks. mkd: T25S R2W S20 BT

A fir, 30" dia. bears N.45°W. 46 lks. mkd: T25S R2W S17 BT

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13233)

The cor. of sees. 16, 17, 20 & 21, monumented with a basalt stone 16x10x8", firmly set 8" in the ground, marked with 3 notches on the S & 4 notches on the E edge, from which the only remaining original bearing tree:

A fir, 40" dia., bears N.48°W., 48 lks., with a healed blaze. (Record bearing and distance, N.45°W., 46 lks.)

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground & in a mound of stone, 2 ft. base, to top, with brass cap marked

T25S	R2W
<u>S 17</u>	<u>S 16</u>
<u>S 20</u>	<u>S 21</u>
1962	

from which new bearing trees

A chinquapin, 9" dia., bears N.17¼°E., 17 lks., mkd T25S R2W S16 BT.

A hemlock, 13" dia., bears S.77°E., 59½ lks., mkd T25S R2W S21 BT.

A cedar, 21" dia., bears S.87°W., 54 lks., mkd T25S R2W S20 BT.

Deposit the original corner stone alongside the iron post.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed May 2001/June 2002- (DCSO rec. Vol. 54 Page(s) 20933-4)

The cor. of secs. 16, 17, 20, & 21, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, in a collar of stone, 2½ ft. base, with brass cap (properly) mkd. from which an original bearing tree continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 32" dia., bears N.48°W., 31.7 ft. with healed blaze and the remains of bearing trees mkd. by Brooks
A chinquapin, 14" dia., bears N.17¼°E., 11.2 ft., with healed blaze.
A dead hemlock, 15" dia., bears S.74½°E., 39.3 ft., with a healed blaze. (Record, S.77°E.)
A cedar, 23" dia. bears S.87°W., 35.6 ft. with fragmentary scribe marks visible on partially healed blaze.
and new bearing tree
A hemlock, 14" dia., bears S.29°E., 9.8 ft., mkd. T25S R2W S21 BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2348, Surveyed Aug. 2011 - (DCSO records BLM Plat T25-2W 2012-1 & Vol. 58 Pages 22940-1)

The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2½" dia., firmly set, flush with the top of a collar of stone, with a brass cap (properly) mkd. from which the remaining original bearing tree
A fir, 38" dia., bears N.48°W., 31.7 ft., with a healed blaze.
and the remains of bearing trees mkd. by Brooks
A chinquapin, 15" dia., bears N.17¼°E., 11.2 ft., with a healed blaze.
A decayed hemlock snag, 15" dia., bears S.74½°E., 39.3 ft., with a healed blaze.
A cedar, 23" dia., bears S.87°W., 35.6 ft., with a healed blaze.
and a bearing tree mkd. by Skeesick in 2001-02
A hemlock, 17" dia., bears S.29°E., 9.8 ft., with scribe marks 25S R2W S21 BT visible on partially healed blaze.
Corner is located 70 ft. E. of a creek, 3 ft. wide, course S.5°E.
Latitude 43°23'15.58"N Longitude 122°57'09.32" W
(NAD 1983 (CORS 96))