

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3634)

Set a basalt stone 16x8x8", 11" in the ground for cor. for cor. of secs. 8, 9, 16, & 17 marked with 4 notches on S & E edges, from which

- A fir, 16" dia. bears N.37°E., 53 lks. mkd: T25S R2W S9 BT
- A hemlock, 4" dia., bears S.21°E., 9 lks., mkd: T25S R2W S16 BT.
- A fir, 4" dia. bears S.25°W., 76 lks. mkd: T25S R2W S17 BT
- A dogwood, 4" dia bears N.45°W. 21 lks mkd: T25S R2W S8 BT

Glen McChesney, WEYCO - 3/24/1959 - C.S. File 53/112-9

-
- Found - 28" fir, old down tree against it, faces not opened - tree leans to East.
- 8" hem. scribing visible in upper face, S.22°E., 5.9 ft. ADDED "W" nail & plate.
 - 8" Fir, chopped out fd. scribing, S.27°W., 48.0 ft.
 - 6" dogwood, scribing visible upper face - lower face not opened, N.47°W., 13.9 ft.
- New - 6" Fir N.25°E., 54.7 ft., "W" nail & plate.
- 32" Fir S.51°W., 47.8 ft., "W" nail & plate.
 - 38" sugar pine (school mar'm) N.23°W., 31.7 ft, "W" nail & plate.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13234)

The cor. of secs. 8, 9, 16 & 17, determined at record bearing & dist. from the original bearing trees:

- A fir, 25" dia. bears N.37°E., 53 lks. with a healed blaze
- A hemlock, 9" dia., bears S.21°E., 9 lks., with scribe marks 25S R2W S1 visible on opened blaze.
- A fir, 9" dia., bears S.25°W., 76 lks., with fragmentary scribe marks visible on opened blaze.
- A dogwood, 6" dia. bears N.45°W., 21 lks. with fragmentary scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 20" in the ground, & in a mound of stone, 3 ft. base, to top, with brass cap mkd

T25S	R2W
S 8	S 9
S 17	S 16
1962	

from which new bearing trees and a bearing object

A fir, 38" dia bears S.14½°E. 41 lks mkd T25S R2W S16 BT CONT

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

The E. face of a rock outcrop, bears S.57¾°W., 14 lks. mkd X BO.
A cedar, 25" dia. bears N.9°W. 58½ lks. mkd T255 R2W S8 BT

David Edwards - 12/2009 - C.S. File 65/66-56

Found - 1962 BLM Brass Cap (properly mkd).
Orig. BT: 36" dia. Fir bears N.37°E., 35.0 ft. Orig. Hemlock is a windfall.
Orig. Fir to SW is a stump. Orig. Dogwood is gone.
1962 BT: a 38" dia. Fir bears S.14½°E. 27.1 ft with healed blaze.
1962 Cedar B.T. to NW is a windfall.
Did not look for X BO in rock outcrop.

New - A 6" dia. Cedar scribed "T25S R2W S8 BT" bears N.50°W., 32.5 ft.
A 6 ft steel post is set 2' East.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2348, Surveyed Aug. 2011 - (DCSO records BLM Plat T25-2W 2012-1 & Vol. 58 Pages 22940-1)

The cor. of secs. 8, 9, 16, and 17, perpetuated by Edwards, in 2009, monumented with an iron post, 2½" dia., firmly set, projecting 2" above the top of a mound of stone, 3 ft. dia., 1 ft. high, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A fir, 39" dia., bears N.37°E., 35.0 ft., with a healed blaze.
A roothole bears S.21°E., 5.9 ft., downhill of which is a fallen, decayed, hemlock snag, 9" dia., with scribe marks 25S R2W S visible on a partially healed blaze.
and the remains of BTs mkd. McChesney, Weyerhaeuser, in 1959
A fir, 17" dia., bears N.22¾°E., 54,7 ft., with a healed double blaze.
A sawed, decayed, fir stump, 36" dia., bears S.50°W., 49.5 ft., with no marks visible on an opened decayed blaze.
and the remains of a BT and a bearing object mkd. by Brooks
A fir, 43" dia., bears S.14½°E., 27.1 ft., with a healed blaze.
An X BO chiseled into the E. face of a rock outcropping bears S.57¾°W., 9.2 ft.
and a bearing tree mkd. by Edwards
A cedar, 8" dia., bears N.48°W., 32.0 ft., with scribe marks T25S R2W SB BT visible on partially healed blaze.
A search was made for all original line trees bet. secs. 8 and 17 and none were recovered.

CONT

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23340)

The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2½" dia., firmly set, projecting 2" above a mound of stone, 3 ft dia. base, 1 ft high, with a brass cap (properly) mkd. from which the remaining original bearing tree

A D.Fir, 39" dia., bears N.37°E., 35.0 ft., with a healed blaze.

and a BT mkd. by McChesney, Weyerhaeuser Timber Co., in 1959

A D.Fir, 18" dia., bears N.22¾°E., 54.7 ft., with a healed double blaze.

and accessories mkd. by Brooks in 1962

A D.Fir, 46" dia., bears S.14½°E., 27.1 ft., with a healed blaze and a large S scribed in the bark.

An XBO chiseled into the E. face of a rock outcrop bears S.57¾°W., 9.2 ft.

and a bearing tree mkd. by Edwards, PLS No. 2339, in 2009

A red cedar, 9" dia., bears N.48°W., 32.0 ft., with scribe marks T25S R2W S8 BT visible on a partially healed blaze.