

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3636)

Set basalt stone 20x10x6", 15" in the ground for ¼ sec. cor. marked ¼ on W face, from which
A hemlock, 12" dia., bears S.70°E., 10 lks., mkd: ¼ S9 BT.
A dogwood, 6" dia., bears S.30½°W., 13 lks., mkd: ¼ S8 BT.

FD. stone & 1 live BT by V. Hosford Aug/Oct. 1958 C.S. File 42/398

Glen McChesney, WEYCO - 3/24/1959 - C.S. File 53/112-6

Found - 18" hemlock, 2 faces not opened recently, S.71°E., 6.2 ft. (ADDED "W" nail & plate)
10"x3' dogwood stub & new 4" sprouts coming up from root, S.31°W., 8.6 ft
New - 16" sugar pine, N.47°W., 15.4 ft. "W" nail & plate.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13235)

The ¼ sec. cor, of secs. 8 & 9, monumented with a basalt stone, 20x10x8", firmly set 15" in the ground, mkd on the W face, from which the original bearing trees:
A hemlock, 25" dia., bears S.70°E., 10 lks, with a healed blaze.
A dogwood crown, bears S.30½°W., 13 lks., with fragmentary scribe marks, in negative, visible on rotted trunk,
At the corner point
Set an iron post, 28" long, 2½" dia., 26" in the ground with brass cap marked
¼
S 8 | S 9
T25S R2W
1962
from which a new bearing tree
A W.Pine, 19" dia., bears N.49¼°W., 25 lks., mkd S8 BT.
Deposit the original corner stone alongside the iron post.

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23341)

The ¼ sec. cor. of secs. 8 and 9, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with a brass cap (properly) mkd.
continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of a BT mkd. by McChesney, Weyerhaeuser Timber Co., in 1959 and reported by Brooks in 1962 as a new bearing tree

A decayed sugar pine stump, 20" dia., bears N.44¼°W., 16.5 ft., with scribe marks ¼ S8 BT visible on a decayed blaze. (Record, white pine, N.49½°W.)

and new bearing trees

A D.Fir, 12" dia., bears S.88½°E., 9.1 ft., mkd. ¼ S9 BT.

A D.Fir, 8" dia., bears N.3°W., 4.6 ft., mkd. ¼ S8 BT.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flaese and Jeff Lorsung -1/7/2026 - C.S. File 67/61-60

Found - ¾" BLM brass cap proj. 6" in rough mound of stone.

¼
S 8 | S 9
T25S R2W
1962

Burned - broken 13" x 12 ft. D. Fir snag N.85°E. 9.0 ft. (Rec S.88½°E. 9.1 ft.) partly healed single blaze. Illegible scribes visible.

13" x 12 ft. 9" D. Fir way out of position downhill. No root hole. Partly healed single blaze, illegible scribes visible.

New - ⅝" x 30" iron with D.C.S.O. plastic cap, proj. 2" N.24°E. 9.1 ft.

Burned - broken off 13" x 6 ft. D. Fir snag S.32°E. 27.5 ft.

Burned - broken off 12" x 5 ft. D. Fir snag N.18°W. 15.1 ft.

Both new BT's have ¾" mag nail right side center.

Notes - Area burnt 9/2020

Mon. on steeper N.W. slope approx. 165 ft. west of gravel rd.

Compass decl. 14¼°E.

TRIMBLE GEO XT POSITION

43.40968587 N.

122.95322825 W.