

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3636)

-----  
Set a basalt stone 17x10x8", 12" in the ground for cor. for cor. of secs. 4, 5, 8, & 9 marked with 5 notch on S & 4 notches on E edges, from which

A cedar, 26" dia., bears N.54°E., 37 lks., mkd: T25S R2W S4 BT.

A hemlock, 9" dia., bears S.31°E., 30 lks., mkd: T25S R2W S9 BT.

A maple, 4" dia. bears S.37°W. 32 lks. mkd: T25S R2W S8 BT

A maple, 7" dia. bears N.63°W. 11 lks. mkd: T25S R2W S5 BT

FD. BC & 4 BTs by V. Hosford Aug/Oct. 1958 C.S. File 42/398

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13351)

-----  
The cor. of secs. 4, 5, 8, & 9, determined at record distance from the original NE & NW bearing trees:

A cedar, 30" dia., bears N.59½°E., 37 lks. blaze partially healed, partial scribe marks visible. (Rec bearing, N.54°E.)

A maple, 10" dia., bears N.83½°W., 11 lks., blaze rotted. (Record bearing, N.63°W.)

At the corner point

Set an iron post, 36" long, 2" dia., 28" in the ground, with brass cap mkd:

T25S R2W
<u>S 5   S 4</u>
S 8   S 9
1951

from which

A hemlock, 10" dia., bears N.20½°W., 38 lks., mkd: ¼ S5 BT

A cedar, 30" dia., bears S.11°E., 36 lks., mkd: ¼ S9 BT.

A cedar, 12" dia., bears S.20½°W., 43 lks., mkd: ¼ S8 BT.

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23341-2)

-----  
The cor. of secs. 4, 5, 8, & 9, monumented with an iron post, 2" dia., firmly set, projecting 14" above the ground, with a brass cap (properly) mkd.

from which the remaining original bearing trees

A red cedar, 51" dia., bears N.59½°E., 24.4 ft., with a healed blaze. continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A maple, 16" dia., bears N.83½°W., 7.3 ft., with a healed blaze.  
and new bearing trees  
A D.Fir, 8" dia., bears S.69¼°E., 15.5 ft., mkd. T25S R2W S9 BT.  
A cedar, 21" dia., bears S.45°W., 28.8 ft., mkd. T25S R2W S8 BT.