

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2870-71)

Set post 4 ft. long, 4" sq., 24" in ground for cor. to secs. 4, 5, 32 and 33 marked T24S S33 on NE.; R2W S4 on SE.; T25S S5 on SW.; S32 on NW. faces, with 2 notches on W. and 4 notches on E. edges, from which
A Fir 48" dia., bears N.65°E., 25 lks. dist. mkd. T24S R2W S33 BT.
A Yew 12" dia., bears S.15°E., 50 lks. dist. mkd. T25S R2W S4 BT.
A Fir 24" dia., bears S.40°W., 75 lks. dist. mkd. T25S R2W S5 BT.
A Yew 14" dia., bears N.40°W., 25 lks. dist. mkd. T24S R2W S32 BT.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13281)

"The intermediate corners along this line which were established by McQuinn formerly referred only to T. 24 S., R. 2 W. The purported retracement of the south boundary of sec. 31 and the reported establishment of closing corners on the boundary by Hezekiah Johnson in 1900 **having proved to be fictitious**, the McQuinn corners except for the south ¼ sec. cor. of sec.31 and the south ¼ sec. cor. of sec. 36, are changed in 1963 to corners of maximum control in order to provide a basis for Consent Decree "Civil No. 60-135, Oregon." (Hezekiah Johnson fictitious corner on Page 3638) The cor. of secs. 32 and 33, determined from the original bearing trees:

- A Fir 50" dia., bears N.65°E., 36 lks. dist., with old bark blaze, breast high, and partial scribe marks. I reblaze and remark T24S R2W S33 BT. (1951) (Rec. dist. 25 lks.)
- A Yew 22" dia., bears S.20°W., 48 lks. dist. with scribe marks S5 BT visible. I reblaze and remark "T25S R2W S5 BT". (1963) (Rec. brg. S.15°E., 50 lks. dist.)
- A Fir snag 37" dia., bears S.40°W., 75 lks. dist., with partial scribe marks in old bark blaze.
- A Yew 20" dia., bears N.26½°W., 25 lks. dist., with scribe marks S 2R visible. I reblaze and remark T24S R2W S32 BT. (1951) (Rec. brg. N.40°W.)

This now becomes the cor. of secs. 4, 5, 32 and 33.
(Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33, T24-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

At the corner point
Set an iron post 36" long, 2" dia., 24" in the ground to
solid rock and in a mound of stone, 4 ft. base to top, with
brass cap mkd. T 24 S | R 2 W
 S 32 | S 33
 S 51 S 4
 T 25 S
 1951
from which a bearing tree mkd. in 1963:
 A Fir 40" dia., bears S.41½°E., 70 lks. dist. mkd. T25S
 R2W S4 BT.

Glen McChesney - Weyerhaeuser Co. - Dec. 20, 1975 - C.S. File
59/46-74

Found 1951 GLO brass cap. Found original BTs, remarked 1951
and 1963:
 50" Fir stump, scribing visible, N.65°E., 23.8 ft.
 22" Yew, scribing visible. BLM BT tag., S.20°W., 31.7 ft.
 37" now 40" Fir snag, partial bark scribing, S.40°W., 49.5
 ft.
 20" Yew, scribing visible, N.26°W., 16.5 ft.
 40" Fir stump, scribing visible BLM, BT tag (1963),
 S.42°E., 46.5 ft.
1950 Weyerhaeuser survey record by D. Calder & R.D. Watson:
Set 1½" Iron pipe and put "W" nails & plates on:
 48" Fir, N.71°E., 25.2 ft. (W. Co. plate gone, W nail
 overgrown. BLM BT tag)
 39" Fir S.23°E., 38.8 ft. (40" Fir stump, plate & W nail
 removed.)
 20" Yew S.16°W., 28.8 ft. (Plate removed, new reference to
 W. nail.)
 16" Yew N.15°W., 15.1 ft. (BLM BT tag & new reference
 refer to GLO brass cap.)
Removed pipe and accessories referring to pipe. Placed 1"
Pipe alongside found brass cap, on mound of stone.
Accessories added this date:
 58" Fir stump, S.88°E., 9.0 ft. with "W" nail & plate.
 20" Yew, S.20°W., 30.5 ft. with "W" nail and plate.
 20" Yew, N.27°W., 15.3 ft. with "W" nail and plate.

Douglas Co. Surveyors Office - Gary L. Langlitz; S. Flause;
F. Silagy, crew - April 3, 1978 - C.S. File 59/46-74

Found - 1951 GLO survey brass cap and 1½" I.P. set by Caler
 & Watson (Weyerhaeuser). Both monuments are out
 of position, displaced by logging activity.
(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A 48" D.Fir now 54" stump, (OBT, 1883) with rescribing "T24S R2W S33 BT" visible on unhealed blaze, bears N.65°E., 23.8 ft. (Rec. N.65°E., 16.5 ft.)

An orig. 12" now 22" Yew (OBT, 1883) alive with rescribing "T25S R2W S5 BT" visible on unhealed blaze. (No orig. scribing found.), bears S.20°W., 31.7 ft. (Rec. S.15°E., 33.0 ft.)

An orig. 24" D.Fir now a 37" snag (OBT, 1883) no scribing found, bears S.42°W., 49.5 ft. (Rec. S.40°E., 49.5 ft.)

An orig. 14" now 20" Yew (OBT, 1883) alive with faint scribing "B" visible on orig. blaze and rescribing "T24S R2W S32 BT" visible on unhealed blaze, bears N.26½°W., 16.5 ft. (Rec. N.40°W. 16.5 ft.)

We do not find the SE. BT marked in 1963, a 40" Fir. At a location which agrees with the previously described BT, WE RESET the 1951 GLO monument, a 2" x 36" I.P., 30" in the ground, with brass cap attached, mkd. as described in the official record. WE ADD the markings "CS 1978" to the brass cap and place the 1½" I.P. alongside the brass cap, extending 18" above ground.

We confirm the bearings and distances to the accessories referenced by Weyerhaeuser Co. as shown on Pg. 3 of the notes filed in C.S. 59/46 with the following exception:

A 20" Yew "W" nail bears S.20°W., 30.1 ft. (Wey. Co. record, S.20°W., 30.5 ft.)

Ron Rice, NW Land Surveying - Jason Collver - Sept. 6, 2012 - C.S. File 65/77-39

Found - 2" dia. Iron post with BLM brass cap dated 1963 and 1978 with 1½ iron pipe alongside.

58" Fir stump, S.88°E., 9.0 ft. with "W" nail & plate. (Found 58" stump with nail and plate)

A 54" stump, with rescribing "T24S R2W S33 BT" visible on unhealed blaze, bears N.65°E., 23.8 ft. (Found 54" stump with scribing visible)

A 37" snag, no scribing found, bears S.42°W., 49.5 ft. (Found 37" stump)

A 20" Yew with faint scribing "B" visible on orig. blaze and rescribing "T24S R2W S32 BT" visible on unhealed blaze, bears N.26½°W., 16.5 ft. (Fd 20" Yew with scribing visible)

A 20" Yew "W" nail bears S.20°W., 30.1 ft. (Fd 23" Yew with nail)

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33, T24-2

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New - 15" D.Fir bears S.18°E., 25.5 ft., scribed T25S R2W
S4 BT
12" Hemlock bears N.46°E., 19.1 ft., scribed T24S
R2W S33 BT
Note - Corner has steel post adjacent to it. All BTs have
red painted bands and yellow tags.
Declination 16° East