

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION South ¼ Sec 33 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2919, surveyed May 2018/July 2020 Approved 3/2021 - (DCS0 records Vol. 59 Page(s) 23913)

-----  
Point for the ¼ sec. cor. of sec. 33 only, on the S. bdy. of T25S R2W.

Set a stainless steel post, 28 ins. long, 2½" dia., 24" in the ground, with brass cap mkd.

T25S R2W  
¼ S 33  
-----  
T26S  
2018

from which

A fir, 14" dia., bears N.43½°E., 6.8 ft., mkd. ¼ S33 BT.

A fir, 13" dia., bears N.59¾°W., 7.9 ft., mkd. X BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

Ron Quimby - Crew: N. Fromdahl, L. Heddens & J. Ogden - 10/2020 - C.S. File 65/106-54

-----  
Found - BLM brass cap (not approved yet) cap mkd:

US DEPARTMENT OF THE INTERIOR

T25S R2W  
¼ S33  
-----  
T26S  
2018

BUR. OF LAND MANAGEMENT

14" burnt Fir N.43°E., 6.8 ft., illegible scribes

14" burnt Fir N.60°W., 7.9 ft., illegible scribes

New - 5/8"x30" I.Rod with yellow plastic cap stamped "ie ENGINEERING" post along side.

S.80°E., 7.5'; S.6°E., 7.2'; S.45°W., 6.4'

Note - Area badly burnt 9/2020

Compass decl. 15½°E.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 9/23/2025 - C.S. File 67/61-27

-----  
Found - 3¼" BLM brass cap on 2" I.D. Iron pipe, proj 8".

15" burnt D. Fir N.43°E. 7.0 ft. (Rec 6.8 ft.)

partial scribe, ¼ on partly healed single blaze.

Continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION South ¼ Sec 33 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

14" burnt D. Fir N.60°W. 7.6 ft. (Rec 7.9 ft.) Scribes  
"¼ S33 BT" visible on partly healed single blaze.  
3 - Iron rods with i.e. Engineering plastic caps.  
    N.63°E. 4.2 ft. proj. 6"  
    S.49°W. 8.0 ft. proj. 3"  
    N.46°W. 5.5 ft. proj. 2"  
Alum. posts 0.3 ft. West and 0.2 ft. East of brass cap.  
Notes - Mon on moderate East slope. Burnt timber North,  
        burnt recent clearcut South.  
Compass decl. 14¼°E.  
OCRS COORDINATE SYSTEM  
COTTAGE GROVE-CANYONVILLE ZONE  
43°20'37.83854" N.  
123°56'35.31764" W.