

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3631)  
-----  
Set basalt stone 18x10x8", 12" in the ground for ¼ sec. cor. marked ¼ on N face, from which  
    A fir, 30" dia., bears S.21°E., 45 lks., mkd: ¼ S28 BT.  
    A maple, 10" dia., bears N.15°E., 59 lks., mkd: ¼ S21 BT.

A. Boyer - Geo. Piper - Aug. 17, 1943 - C.S. File 31/18  
-----  
Found - Decayed remains of OBT - 10" Maple & 30" Fir.  
          Orig. (mkd ¼ N face) rock.  
New - 30" Fir N.87°E., 19.7'  
      10" Maple S.13½°E., 35'

V.W. Hosford - Sept. 1957 - C.S. file 42/308-4  
-----  
After logging in section 21, I found the orig. marked stone corner in place. The original BT for Sec 21 is down & badly rotted. The orig BT for Sec. 28 is a rotten stub showing an old face but with scribing rotted away. The Co. Surveyor's BT for Sec 28 is living. I drove 1½" iron pipe 36" long 18" in the ground on the West edge of the corner stone, from which:  
    A Maple 12" in dia. bears S.13½°E., 34.3 ft. (County Surveyor's BT not re-marked)  
    A Hemlock 10" in dia., bears N.61°W., 21.0 ft. marked ¼ S21 253 BT.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13231-2)  
-----  
The ¼ sec. cor. of secs. 21 & 28, monumented with a basalt stone, 18x10x8" firmly set 11", in the ground, mkd ¼ on the N face, perpetuated & recorded by Hosford in 1957, with an iron pipe, 36" long, 1½" dia., 12" in the ground alongside the original corner stone, from which the only remaining original bearing tree:  
    A rotted fir stump, 34" dia., bears S.25½°E., 47 lks. with no marks remaining. (Rec bearing & distance, S.21°E., 45 lks.)  
and trees marked by Boyer, County Surveyor, in 1913.  
    A down & rotted fir, 30" dia., bears N.87°E., 30 lks., with no marks remaining.  
    A maple, 14" dia., bears S.14½°E., 52½ lks., with scribe marks ¼ S 8 BT visible on partly healed double blaze.  
and a tree marked by V. W. Hosford, in 1957  
continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A down hemlock, 11" dia., bears N.61°W., 32 lks., with scribe marks ¼ S21 253 BT visible on unhealed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground with brass cap marked

¼  $\frac{S\ 21}{S\ 28}$   
T25S R2W  
1962

from which a new bearing tree

A hemlock 6" dia., bears N.50°W., 12 lks., mkd ¼ S21 BT. Deposit the original corner stone and reset the iron pipe alongside the iron post

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed May 2001/June 2002- (DCS0 rec. Vol. 54 Page(s) 20930-1)

-----  
The ¼ sec. cor. of secs. 21 & 28, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with original stone buried alongside, and an iron pipe, 2" dia., driven alongside, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A decayed fir stump, size indeterminate, bears S.25½°E., 31.0 ft., with no marks visible.

and remains of BTs mkd. by Boyer in 1943 & reported by Brooks

A decayed fir stump, size indeterminate, bears N.87°E., 19.8 ft., with no marks visible.

A decayed maple stump, size indeterminate, bears S.14½°E., 34.6 ft., with no marks visible.

and remains of a BT by Hosford, in 1957 & reported by Brooks

A roothole, bears N.61°W., 21.1 ft.

and remains of a bearing tree mkd. by Brooks

A roothole, bears N.50°W., 7.9 ft.

and new bearing trees

A cedar, 10" dia., bears N.31½°E., 22.8 ft., mkd. ¼ S21 BT

A hemlock, 14" dia. bears S.33½°E., 26.3 ft. mkd. ¼ S28 BT

Ken Hoffine - For: Lone Rock Timber Co - Jan. 2020 - C.S. File 65/105-12

-----  
Found - 1962 BLM brass cap marked ¼ S21|S28 T25S R2W  
10" Western Red Cedar fd at record N.31½°E 22.8' tag and healed face.

14" Hemlock now a stump found at record S.33½°E., 26.3'. tag and healed face.

Did not search for other stumps or root holes.

Brass cap lies on flat ground. 1½" iron pipe and stone beside. aluminum l post bears west 1 foot.