

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3633)</p> <p>-----</p> <p>Set washed boulder 20x14x8", 15" in the ground for ¼ sec. cor. marked ¼ on N face, from which</p> <p>    A fir, 16" dia., bears S.39°E., 39 lks., mkd: ¼ S21 BT.</p> <p>    A fir, 16" dia., bears N.46°E., 33 lks., mkd: ¼ S16 BT.</p>
<p>Douglas Co. Surveyors Office - B.B. Irving, Co. Surveyor - A.R. Evans, Deputy - Wit: Milo Godfrey, Les Kershner, J.I. Clinton - Feb. 1948 - C.S. File 39/169 &amp; M 12-34</p> <p>-----</p> <p>Found - Rock noted in official notes gone.</p> <p>        Stump 20" Fir S.39°W., 29 lks. (17.1 ft.) with old scribe mks S21 visible. BT scar not chopped out.</p> <p>        OBT N.46°E., 33 lks., (22 ft.) stump knocked out. Old blaze badly burned BT scar not chopped.</p> <p>Set - 1"x36" iron pipe with brass cap in ground mkd: Co. Surveyor Office T25S R2W ¼ S16/21</p> <p>        36" Fir N.41½°W., 34.7 ft. ¼ S16 CS BT.</p> <p>        24" Cedar S.34½°W., 223.5 ft. mkd: ¼ S21 CS BT.</p>
<p>Douglas Co. Surveyors Office - James Byron - M Godfrey - C Putnam - July 13, 1960 - C.S. File 49/102-6</p> <p>-----</p> <p>Found - Brass cap at corner. 1948</p> <p>        SW BT is ok, shows good scribing.</p> <p>        NW BT is gone in new roadway construction.</p> <p>New BT - 22" Cedar bears N.57°E. 65.0 ft. scribed ¼ S16 CS BT</p>
<p>FD ok by BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13233)</p>
<p>Douglas County Surveyors Office - Randal Smith &amp; Stephen Flause - 4/4/95 - C.S. 64/63-4</p> <p>-----</p> <p>Found - 2½" DCSO Brass cap on a 1½" OD Iron pipe protrudes 7" above ground. Brass cap is orientated NE &amp; is surrounded by a 2½' dia mound of stone.</p> <p>        Orig. stone laying on side, measures 20"x14"x8", with marks "¼" found, bears N.41°W., 1.2' from BC/IP. Brg. &amp; Dist. taken to center of stone.</p> <p>        16" now 20" dia, 2½' high rotted D.Fir stump, with scribing visible "S21", bears S.39°E., 17.1'.</p> <p>continued next page</p>

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

24" now 33" dia Cedar, with a unhealed blaze no scribing visible. We double blaze and rescribed "¼ S21 CS BT", bears S.34½°W., 223.5'.  
 22" now 35" dia R.Cedar, with a fully healed double blaze, bears N.57°E., 64.1'.  
 New - 10" dia D.Fir, double blazed & scribed "¼ S21 CS BT" bears S.41°W., 26.8'.  
 15" dia D.Fir, double blazed & scribed "¼ S16 CS BT" bears N.29°E., 28.6'.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed May 2001/June 2002- (DCS0 rec. Vol. 54 Page(s) 20934-5)  
 -----  
 The ¼ sec. cor. of secs. 16 & 21, monumented with an iron post, 1½" dia., firmly set, projecting 6" above ground, in a collar of stone, with brass cap mkd.  
 COUNTY SURVEYORS  
 T 25 S  
 1/4 S 16 | S 21  
 R 2 W |  
 BLM  
 OFFICE 1962  
 from which a BT mkd. by Irving, in 1948, reported by Brooks  
 A cedar, 34" dia bears S.35¼°W. 223.7 ft with healed blaze and BT mkd. by Byron, in 1960, reported by Brooks  
 A cedar, 38" dia. bears N.58°E. 65.3 ft. with healed blaze and bearing trees mkd. by Smith & Flause, in 1995  
 A fir, 17" dia., bears N.30°E., 28.8 ft. with healed blaze  
 A fir, 11" dia., bears S.42°W., 27.0 ft. with healed blaze

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 9/27/2022 - C.S. File 67/54-21  
 -----  
 Found - 2½" DCS0 brass cap on 1½" I.Pipe up 8"  
 Burnt-dead 34" Cedar S.35¼°W., 223.7 rec. healed blaze. 1948  
 38" Cedar N.56°E., 64.3 ft. (Rec. N.58°E., 65.3 ft.) healed blaze, add 3½" mag nail right side center. 1960  
 Burnt-sawn 19"x1½' fir stump N.29°E., 29.0 ft. (rec N.30°E., 28.8 ft.) 3½" mag nail top center blaze in stump. 1960  
 13"x7½' fir stump S.41°W., 27.1 ft. (rec. S.42°W., 27.0 ft) add 3½" mag nail top center blaze in stump. 1960  
 Alum. angle iron post 1 ft E & W. Cont.

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Note - Corner is 50±' east of paved Rock Ck Rd.  
Area burnt 9/2020  
Compass decl. 14½°E.  
Lat: 43°23.18.09"N Long: 122°56'37.26"W