

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION C C for Secs. 33 & 34 only, (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 9 Page(s) 3616)

At point of intersection (4.62 chs. W. of the cor. of secs. 3, 4, 33 and 34) I Set a basalt stone 18x10x6 ins., 12" in the ground for closing cor. of secs. 33 and 34, marked C C with 3 notches on E. and W. edges and raised a mound of stone 2 ft. base, 1½ ft. high, N. of cor. Pits impracticable.

Survey by G. Robert Lecklider - For: Evans Products Co. - Aug. 1960 - M 19-40

Found Corner stone, mound of stone, N. 3 ft.
Set steel tube with survey cap, from which
16" Fir N.12°E., 17.4 ft.
12" Fir N.15°W., 10.5 ft.

BLM Resurvey by Daniel Berry; Harvey Wofford; G. Steven Popken, Cadastral Surveyors, under Group #'s 786, 848 and 854. And Glenn S. Baughman, L.S. #536, under Contract #52500-CT5-1116, Surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15122)

(39.17 chs.)
The orig. closing cor. of secs. 33 & 34, perpetuated and recorded by Lecklider in 1960, monumented with the original basalt stone, 18x10x6 ins., firmly set, in a mound of stone, 2 ft. base, 1 ft. high, mkd. CC on N., 3 notches on W., and 3 notches on E. face, from which bearing trees mkd. by Lecklider;
A Fir 17" dia., bears N.12°E., 26½ lks. dist. with healed blaze.
A Fir 13" dia., bears N.15°W., 16 lks. dist. with healed blaze.

I add marks AM to stone.
(40.63 chs.) (S.0°23'W.)
Intersect the N. bdy. of Sec. 4, T26S R2W.
Set an Iron post 28" long, 2½" dia., 22" in the ground, with brass cap mkd.
C C
T 25 S R 2 W
S 33 | S 34
S 4
T 26 S R 2 W
1974

from which
(Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION C C for Secs 33 & 34 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 14" dia., bears N.42 3/4°E., 17 lks. dist. mkd. T25S R2W S34 CC BT.
A Fir 14" dia., bears N.40°W., 50 lks. dist. mkd. T25S R2W S33 CC BT.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor and Robert H. Browning, Survey Technician, under Group #1754, surveyed May 1995 - July 1998 - (DCSO records Vol. 53 Page(s) 20453-4)

Mark Smalley - For: Roseburg Resources - June 2003 - C.S. File 65/48-9

Found - BLM steel pipe & brass cap (properly mkd)
22" Fir N.42 3/4°E., 11.2' healed.
22" Fir N.40°W., 33.0' healed.
1/2" I.D. IP bent with 1" BC marked "PROPERTY CORNER"
96.63' North along line.
26" Fir N.12°E., 17.4' healed.
16" Fir N.15°W., 10.5' down healed.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2919, surveyed May 2018/July 2020 - (DCSO records Vol. 59 Page(s) 23911-2)

The true closing cor. of secs. 33 and 34, T25S R2W monumented with an iron post, 2 1/2" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd. from which the remains of BTs mkd. by Berry, Wofford, Popken, and Baughman in 1972-75
A fir stump, 22" dia., bears N.42 3/4°E., 11.2 ft., with a healed blaze.
A fir snag, 22" dia., bears N.40°W., 33.0 ft., with a healed double blaze.
and new bearing trees
A fir, 7" dia., bears N.31°E., 22.9 ft., mkd. T25S R2W CC S34 BT.
A fir, 7" dia., bears N.52 1/4°W., 19.6 ft., mkd. T25S R2W CC S33 BT.

From this cor., the original closing cor. of secs. 33 and 34, T25S R2W bears N.0°10'44"W., 96.56 ft.; monumented with an iron post, 5/8" dia. (Record, pipe, 1/2" dia.), firmly set, projecting 15" above ground, in a mound of stone, 3 ft. base, 6". high, bent at a 45 degree angle to the SW, with aluminum cap mkd. PROPERTY CORNER, from which the remains of the BTs mkd. by Lecklider, in 1960, reported by Seibold and Browning in 1995-98,

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION C C for Secs. 33 & 34 only, (South)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir stump, 26" dia., bears N.12°E., 17.5 ft., no marks visible.

A roothole bears N.15°W., 10.6 ft., alongside of which is a down fir, 16" dia., with a healed blaze. (Record, N.25°W., 7.3 ft.)

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

Corner is located E., 20 ft., of a graveled road, 18 ft. wide, bears S.60°E. and N.35°W.

NAD1983 (2011)

Lat: 43°20'37.60 N Long: 122°56'01.00" W

I.E. Engineering and Douglas Co. Surveyors Office - Crew: N. Fromdahl, Stephen Flause & Jeff Lorsung- 12/9/2021 (Filed 4/12/2022) - C.S. File 67/52-6

Found - BLM brass cap (properly mkd), 1974
Orig. Corner stone.
Burnt 23" Fir N.40°W., 33.3 ft. (rec. 33.0) to nail
Rt side center healed scar.
Burnt rotted 7" fir snag N.42¾°E., 11.3 ft to nail
Rt side center (Rec. 11.2 ft) healed scar.
2018 (BLM) BT 6"x3' Fir stump N.30°E., 23.0 ft. vis.
scribes T25S R2W S34 BT.
3 - 5/8"x30" iron rods with I.E. Yellow Plastic cap
marked: ie ENGINEERING
N.43°E., 9.0 ft.
S.30°W., 6.8 ft.
N.40°W., 30.1 ft.
Orig. CC perpetuated by Lecklider, ½" IP w/1" BC
protruding 16", North 96.6'

Note - This is a combined renewal of DCS0 & I.E. Engineering.

Area burnt 9/2020

Corner is 20' north & 25' east of graveled road.

Compass decl. 14½°E.

Lat: 43°30'37.68" N Long: 122°56'01.02" W