

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3617)

Set basalt stone 16x8x7", 11" in the ground for ¼ sec. cor. marked ¼ on W faces, from which
A fir, 10" dia., bears N.62°30'E., 80 lks., mkd: ¼ S34 BT.
A fir, 8" dia., bears S.52°W., 50 lks., mkd: ¼ S33 BT.

G. Robert Lecklider - For: Evans Products Co. - Aug. 1960 - M19-40

Found - Corner stone
46" Fir N.62°E., 52.8 ft.
20" Fir S.52°W., 33.0 ft.
Set - 14" Fir N.20°W., 14.5 ft.
14" Fir S.44°E., 14.2 ft.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13223)

The ¼ sec. cor. of secs. 33 & 34, monumented with a basalt stone, 16x12x6", firmly set 11" in the ground, marked ¼ on the W. face, from which the original BTs:
A fir, 14" dia., bears N.64°E., 75½ lks., with a healed blaze. (Record bearing and distance, N.62¼°E., 80 lks.)
A fir, 16" dia., bears S.53°W., 50 lks., with a healed blaze. (Record bearing S.52°W.)
and bearing trees marked by Lecklider in 1960
A fir, 15" dia. bears S.38½°E., 20½ lks. with scribe marks ¼ S34 RE4079 BT visible on unhealed double blaze.
A fir, 12" dia. bears N.23°W., 22 lks., with scribe marks ¼ S33 RE4079 BT visible on unhealed double blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 16" in the ground, to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap marked
¼
S 33|S 34
T 25 S|R 2 W
1962

Deposit the original corner stone alongside the iron post.

Fd. ok by BLM dependent resurvey by Daniel Berry, Harvey Wofford, & Steven Popken Cadastral Surveyors & Glenn Baughman, LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct. 1975 - (DCSO recs Vol. 36 Page 15121)

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Brian S. Seibold, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1754, surveyed May 1995/July 1998 - (DCSO records Vol. 53 Page(s) 20457-8)

The ¼ sec. cor. of secs. 33 & 34, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A fir, 52" dia., bears N.64°E., 75½ lks., with healed blaze.

A root hole, bears S.53°W., 50 lks., with decayed fir trunk, size indeterminate, alongside, with no mks. visible.

and BTs mkd. by Lecklider, in 1960

A fir, 21" dia., bears S.38½°E., 20½ lks., with healed double blazes.

A fir, 15" dia., bears N.23°W., 22 lks., with healed blaze.

Cor. is located E., 0.44 chs. from a ravine, drains N.50°E.