

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3616)

Set a basalt stone 18x9x9", 12" in the ground for cor. for cor. of secs. 27, 28, 33, & 34 marked with 1 notch on S & 3 notches on E edges and raised a mound of stone 2 ft. base, 1½ ft. high, W of cor. Pits impracticable.

G. Robert Lecklider - For: Evans Products Co. - 8/1960 - M19-40

Found - Corner stone - mound stone - West 3 ft.
Set - Steel tube with survey cap
14" S.Pine N.88°E., 119.2 ft.
4" Fir N.9°W., 22.4 ft.
12" Fir S.73°W., 47.1 ft.
12" Fir S.21°E., 52.8 ft.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13223-4)

The cor. of secs. 27, 25, 33 & 34, monumented with the original basalt stone, 18x9x9", firmly set 12" in the ground, marked with 1 notch on the S & 3 notches on the E edge, & witnessed by a mound of stone 2 ft base 1 ft high W of corner from which locally established bearing trees
A W.Pine, 14" dia., bears N.87½°E, 181 lks., with scribe marks RE4079 S27 BT visible on unhealed double blaze.
A Fir, 11 dia., bears S.21°E., 80½ lks., with scribe marks S34 RE4079 BT visible on unhealed double blaze.
A fir, 10" dia., bears S.72½°W., 71 lks., with scribe marks S33 RE4079 visible on unhealed double blaze.
A fir, 5" dia., bears N.9°W., 34 lks., with scribe marks S28 RE4079 BT visible on unhealed double blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
T25S R2W
S 28 | S 27
S 33 | S 34
1962
Deposit the orig. corner stone alongside the iron post.

BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford, & G. Steven Popken Cadastral Surveyors & Glenn S. Baughman, LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct 1975 - (DCSO rec Vol. 36 Pgs 15120-1)

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor Secs 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The cor. of secs. 27, 28, 33, & 34, perpetuated & recorded by Lecklider, in 1960 and remonumented by Brooks, in 1962, with an iron post, 2½" dia., firmly set, protruding 4" above ground, alongside, of which is the orig basalt stone 18x9x9", firmly set, with 1 notch on S & 3 notches on E face, with brass cap (properly) mkd.

from which bearing trees mkd. by Lecklider

A W.Pine, 20" dia., bears N.87½°E., 181 lks., with healed double blaze.

A fir, 17" dia., bears S.21°E., 80½ lks., with healed double blaze.

A fir, 22" dia., bears S.72½°W., 71 lks., with healed double blaze.

A fir, 10" dia., bears N.10¼°W., 34 lks., with healed double blaze.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2919, surveyed May 2018/July 2020 - (DCSO records Vol. 59 Page(s) 23922-3)

The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2½" dia. firmly set, projecting 4" above ground (alongside of which is the original basalt stone, 18x9x9", firmly set, projecting 4" above ground, with no marks visible), with a brass cap (properly) mkd.

from which the remains of the bearing trees mkd. by Lecklider, PE No. 4079, in 1960, reported by Brooks in 1962

A pine stump with broken top, size indeterminate, bears N.87½°E., 119.5 ft., alongside of which is a down pine 21" dia., with scribe marks S27 BT visible on partially healed double blaze.

A fir, 25" dia. bears S.21°E., 53.1 ft with a healed blaze

A fir, 27" dia bears S.72½°W., 46.9 ft with a healed blaze

A fir, 20" dia., bears N.9°W., 22.4 ft with a healed blaze and a new bearing tree

A fir, 13" dia., bears N.66°E., 26.9 ft., mkd. T25S R2W S27 BT.

Bury the original stone alongside the cor.

Corner is located W, 95 ft., of a graveled road, 18 ft. wide, bears N.20°E. and S.30°W.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

NAD 1983 (2011)

Lat: 43°21'30.06" N

Lat: 122°56'00.13" W

CONT.

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor Secs 27, 28, 33, & 34

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 3/1/2022 (Filed 7/21/2022) - C.S. File 67/52-26

Found - 3¼" BLM brass cap (properly mkd) on iron pipe proj. 3". Orig. stone buried on SW side.

BTs by lecklider 1960
26" D.Fir S.21°E., 52.4 ft. (Rec. 53.1) healed double blaze, PK right side center.
27" D.Fir S.72½°W., 47.0 (rec. 46.9) healed double blaze, PK right side center.
22" D.Fir N,10¼°W. 23.0 ft. (Rec 22.4) healed double blaze, PK right side center.

BLM resurvey 2018-2020
14" D.Fir N.65°E., 26.9 ft. scribed T25S R2W S28 BT, PK nail right side center.

Note - Corner is approx 95 ft north & 95 ft west of gravel road.

Area badly burnt 9/2020
See sketch in file.
Compass decl. 14½°E.

Lat: 43°21'30.15" N Long: 122°56'00.15" W