

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3618)

Set a basalt stone 16x8x6", 11" in the ground for cor. for cor. of secs. 21, 22, 27, & 28 marked with 2 notch on S & 3 notches on E edges, from which

A hemlock, 5" dia., bears N.12½°E., 31 lks., mkd: T25S R2W S22 BT.

An arbutus, 6" dia., bears S.80°E., 14 lks., mkd: T25S R2W S27 BT.

A chinquapin, 8" dia., bears S.42°W., 14 lks., mkd: T25S R2W S28 BT.

A fir, 20" dia. bears N.75°W. 51 lks. mkd: T25S R2W S21 BT

Glen McChesney, Weyerhaeuser Co. - 7/30/1958 - C.S. File 53/112-32

Found - Stone

14" hemlock N.11°E., 20.5 ft. GLO

14" chinquapin S.39°W., 9.2 ft. GLO

32" fir N.74°W., 33.7 ft. GLO

SE BT gone.

New - Added "W" nail & plate to existing GLO BTs

10" chinquapin S.86°E., 19.3 ft. with "W" nail & plate.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13225)

The cor. of sees. 21, 22, 27 & 28, monumented with a basalt stone 16x8x6", firmly set 10" in the ground, marked with 2 notches on the S & 3 notches on the E edge, from which the original bearing trees:

A hemlock, 17" dia., bears N.12½°E., 31 lks., with a healed blaze.

A chinquapin snag, 18" dia., bears S.38°W., 14 lks., with a healed blaze. (Record bearing, S.42°W.)

A fir, 37" dia., bears N.75°W., 53 lks., with a healed blaze. (Record distance, 51 lks.)

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

T25S R2W
S 21 | S 22
S 28 | S 27
1962

from which new BTs

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A chinquapin, 8" dia., bears S.62°E., 46 lks., marked T25S R2W S27 BT
A chinquapin, 4" dia., bears S.54½°W., 37½ lks., marked T25S R2W S28 BT.
Deposit the original corner stone alongside and break a clear glass bottle at base of the iron post.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed May 2001/June 2002- (DCSO rec. Vol. 54 Page(s) 20929-30)

The cor. of secs. 21, 22, 27, & 28, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A hemlock, 30" dia., bears N.12½°E., 20.5 ft., with healed blaze.
A decayed chinquapin stump, size indeterminate, bears S.38°W., 9.2 ft., no marks.
A sawed fir stump, 37" dia., bears N.75°W., 39.7 ft., with healed blaze. (Record, 35.0 ft.)
and remains of bearing trees mkd. by Brooks
A chinquapin, 13" dia., bears S.62°E., 30.4 ft., with healed blaze.
A decayed chinquapin stump, size indeterminate, bears S.54½°W., 24.7 ft., no marks.

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749, surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23335)

The cor. of secs. 21, 22, 27, & 28, monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground, with a brass cap (properly) mkd.
from which the remains of the original bearing trees reported by Skeesick in 2001-02
A hemlock, 31" dia., bears N.12½°E., 20.5 ft., with a healed blaze.
A D.Fir stump, 37" dia., bears N.75°W., 33.7 ft., with a healed blaze. (Record, 39.7 ft.)
and remaining BT mkd. by Brooks in 1962, reported by Skeesick
A chinquapin, 13" dia., bears S.62°E., 30.4 ft., with a healed blaze.
and bearing trees mkd. by person(s) unknown
A hemlock, 13" dia., bears S.69°W., 21.2 ft., with scribe marks T25S R2W S28 BT visible on a partially healed blaze.
A D.Fir, 7" dia., bears N.64°W., 29.1 ft with a healed blaze

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Ken Hoffine - For: Lone Rock Timber Co - Jan. 2020 - C.S.
File 65/105-12

Found - 1962 BLM Brass cap marked T25S R2W S21 S22 S28 S27
15" Hemlock found at record S.69°W., 21.2'. visible
scribe and tag.
34" Hemlock found at record N.12½°E., 20.5' healed
face and tag.
15" Chinquapin found at record S.62°E., 30.4' healed
face and tag.
42" D.Fir stump found at record N.75°W., 33.7'.
healed face and tag.
Note - Brass cap lies on gentle south sloping ridge 0.5 ft
above ground.
3 ft tall aluminum l post bears west 0.6 ft