

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3622)

-----  
Set a basalt stone 18x12x8", 12" in the ground for cor. for cor. of secs. 9, 10, 15, & 16 marked with 4 notch on S & 3 notches on E edges, from which

- A fir, 48" dia. bears N.44°E. 17 lks. mkd: T25S R2W S10 BT
- A fir, 20" dia. bears S.29°E. 75 lks. mkd: T25S R2W S15 BT
- A fir, 14" dia. bears S.33°W. 34 lks. mkd: T25S R2W S16 BT
- A fir, 12" dia. bears N.35°W. 40 lks. mkd: T25S R2W S9 BT

Douglas Co. Surveyors Office - B.B. Irving, Co. Surveyor - A.R. Evans, Deputy - Wit: Milo Godfrey, Les Kershner, J.I. Clinton - Feb. 1948 - C.S. File 39/169 & M 12-34

- Found - Rock Corner, identified from OBTs.  
60" Fir, N.44°E., 17 lks.  
14" Fir, N.33°W., 40 lks.  
New BT - 30" Fir, S.5°W., 38.2 ft.  
30" Fir, S.45°E., 50.0 ft.

Glen McChesney, Weyerhaeuser Co. - 2/11/1960 - C.S. File 53/112-15

- Found - Stone under 46" fir blow down.  
56" fir, upper & lower cat faces visible, N.40°E., 11.2 ft. GLO (Added "W" nail & plate)  
24"x5" fir shell-scribed "BT" visible, S.25°E., 46.5 ft. GLO  
SW GLO BT gone.  
14" Fir, upper & lower cat faces visible, N.38°W., 26.4 ft. GLO (Added "W" nail & plate)  
36" fir stump, bark scribing visible S.5°W., 38.8 ft. CS (Added "W" nail & plate)  
42" Fir, stump, bark scribing visible S.33°E., 44.28 ft. CS (Added "W" nail & plate)  
New - 12" hemlock S.3°W., 18.1 ft. "W" nail & plate.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13227-8)

-----  
The cor. of secs. 9, 10, 15, & 16, monumented with a basalt stone 14x10x8" firmly set 10" in the ground mkd with 4 notches on S & 3 notches on E edge, from which the orig BTs  
A fir, 57" dia., bears N.37°E., 20 lks., with a healed blaze. (Record bearing distance, N.44°E., 17 lks.)  
continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A broken fir stump, 26" dia., bears S.26°E., 71 lks., with scribe marks T25S R2W S15 visible on an unhealed blaze on fallen trunk. (Rec bearing & distance, S.29°E., 75 lks.)

A down fir, 14" dia., bears S.33°W., 34 lks. with no marks remaining.

A fir, 15" dia., bears N.40°W., 40 lks., with a healed blaze. (Record bearing, N.35°W.)

and bearing trees marked by Irving, 1958

A fir, 50" dia., bears S.32½°E., 70 lks., marked T25S R2W S15 CS BT, on bark.

A sawed fir stump, 36" dia., bears S.5°W., 61 lks., marked T25S R2W S16 BT, on bark.

At the corner point  
 Set an iron post, 28" long, 2½" dia., 25" in the ground, with brass cap marked:

T25S	R2W
S 9	S 10
S 16	S 15

1962

from which a new BT

A fir, 16" dia. bears S.36°W. 55 lks. mkd: T25S R2W S16 BT

Deposit orig. corner stone alongside the iron post.

The corner falls under a fallen fir, 48" dia.

Fd. Ok 2/1992, G. Lang M114-57

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2348, Surveyed Aug. 2011 - (DCSO records BLM Plat T25-2W 2012-1 & Vol. 58 Pages 22940-1)

-----

The cor. of secs. 9, 10, 15, and 16, monumented with on iron post, 2½" dia., firmly set, top flush with ground surface, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A fir, 57" dia., bears N.37°E., 13.2 ft., with a healed blaze.

A broken fir stump, size indeterminate, bears S.26°E., 46.9 ft., with no marks visible.

A roothole bears N.40°W., 26.4 ft., uphill of which is a fallen, decayed fir, size indeterminate, with no marks visible.

and the remains of BTs mkd. by Irving, in 1948

A fir, 47" dia., bears S.32½°E., 43.6 ft., with scribe mks T25S R2W S15 CS visible on bark blaze (Rec 46.2 ft)

A sawed fir stump, 36" dia., bears S.5°W.. 40.3 ft., with a healed blaze.

and a bearing tree mkd. by Brooks

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir, 25" dia., bears S.36°W., 36.3 ft., with a healed blaze.  
and a new bearing tree  
A cedar, 18" dia., bears N.40¼°W., 50.6 ft., mkd. T25S R2W S9 BT.