

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400542

PRIMARY CORNER DESCRIPTION AP - Line tree between secs. 9 & 10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3624)

From the corner of 9, 10, 15, & 16 I run N.2°W., between secs. 9 & 10, at 42.03 chs. -
A fir, 36" dia., on line, I mark with 2 notches on N and S sides.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13229)

... an original line tree
A fir, 92" dia., bears North, 203 lks., mkd with 2 notches on the N & 2 notches on the S side

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & Crew - June 26, 1972 - C.S. File 54/27

Note - Old line tree N. 135.0 ft., now 80 ft. high snag, notches on N. & S. Sides visible.

Fd. stump found on line north of corner (N.2°15'35"E., 136.0 ft. of ¼ Cor. secs. 9 & 10) 2/1992, M114-57

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23338)

The remains of an original line tree, a fir stump, 84" dia., approximately 4 ft. high, with one notch visible on the S. side, and now functions as an angle point.
At the corner point
Drive an iron rod, 36" long, 5/8" dia., 35" into the center of the stump, with an alum. cap mkd.
T25S R2W
AP
S 9|S 10
2014

Ron Quimby - Crew: L. Heddens & J. Ogden - 10/2020 - C.S. File 65/106-45

Found - Alum. cap on 5/8" I.Rod in top of 84" Fir stump.
Set - 5/8"x30" I.Rods with plastic cap stamped ie engineering: N.35°E., 23.0 ft - N.30°W., 26.0 ft
Post set along side of I.Rods
Note - Area burnt badly 9/2020. Corner is approx 300' south of road.
Compass decl. 15½°E.