

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3626)

Set basalt stone 17x12x5", 12" in the ground for 1/4 sec. cor. marked 1/4 on W face, from which

A hemlock, 6" dia., bears S.43°E., 24 lks., mkd: 1/4 S3 BT.

A hemlock, 18" dia., bears N.42°W., 2 lks., mkd: 1/4 S4 BT.

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13349)

The 1/4 sec. cor. of secs. 3 & 4, monumented with a basalt stone, 14x10x4", firmly set, marked 1/4 on W face, from which the original bearing trees:

A hemlock, 26" dia., bears N.42°W., 3 lks., blaze healed. (Rec distance, 2 lks.)

A hemlock, 8" dia., bears S.56°E., 24 lks., blaze chopped open, scribe marks S3 visible. (Rec bearing, S.43°E.)

At the corner point

Set an iron post, 36" long, 1" dia., 28" in the ground, with brass cap mkd.

1/4
S 4 | S 3
1951

from which

A hemlock, 38" dia., bears S.47°E., 43 lks., mkd. 1/4 S3 BT

Bury the original corner stone alongside the iron post.

Glen McChesney, WEYCO - 8/2/1965 - C.S. File 53/112-1

Found - Stone & 1951 brass cap.

26" hemlock N.42°W., 3 lks., (rec. 2 lks.) face healed over.

8" hemlock S.56°E., 24 lks., scribing visible.

32" hemlock S.47°E., 43 lks., scribing visible.

New - 54" fir S.69°W., 17.5 ft., with "W" nail & plate.

32" hemlock S.46° 26.0 ft. (1951) added "W" nail & plate.

Ron Quimby - Crew: L. Heddens & J. Ogden - 10/2020 - C.S. File 65/106-42

Found - GLO brass cap (properly marked)

Stone gone

Remnant of hemlock stump N.42°W., 2'

Remnant of hemlock stump S.46°E., 26.0

Remnant of fir stump S.69°W., 17.5 ft.

Cont.

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - PK in 20' tall bluff N.64°E., 36.4 ft.
5/8"x30" I.Rods with plastic cap stamped: ie
engineering with post along side:
S.31°E., 11.0 ft.
S.54°W., 7.4 ft.
N.35°W., 46.3 ft.
Note - Compass decl. 15½°E.