

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 34

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

G. Robert Lecklider - For: Evans Products Co. - Aug. 1960 - M19-40

Set - Steel tube with survey cap.
 14" Fir N.63°E., 24.8 ft.
 24" Fir N.73°W., 1.9 ft.

BLM dependent resurvey by Brian S. Seibold, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1754, surveyed May 1995/July 1998 - (DCSO records Vol. 53 Page(s) 20459-60)

The center ¼ sec. cor. of sec. 34, established by Lecklider, and is accepted as the cor.; monumented with an iron pipe, ½" dia., firmly set, projecting 15" above ground, with aluminum cap, 1 in. diam., mkd. "PROPERTY CORNER", from which the remains of bearing trees mkd. by Lecklider

A fir snag, 14" dia., bears N.63°E., 38 lks., with scribe mks. S34 RE 4079 B visible on partially healed double blazes.

A sawed fir stump, 24" dia., bears N.77¼°W., 2½ lks., with fragmentary scribe mks. visible on decayed open blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over the iron pipe, with brass cap mkd.

T 25 S R 2 W

C 1/4 S 34

1995

from which new bearing trees

A fir, 26" dia., bears S.23°E., 47 lks., mkd. C¼ S34 BT.

A hemlock, 27" dia., bears N.86°W., 63 lks. mkd. C¼ S34 BT

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.