

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3615)

Set basalt stone 14x10x8", 10" in the ground for 1/4 sec. cor. marked 1/4 on N faces, from which

A cedar, 6" dia., bears N.54°W., 16 lks., mkd: 1/4 S27 BT.

A hemlock, 4" dia., bears S.21°E., 8 lks., mkd: 1/4 S34 BT.

G. Robert Lecklider - For: Evans Products Co. - Aug. 1960 - M19-40

Found - Corner stone.

9" Cedar N.53°W., 10.6 ft.

12" Cedar S.21°E., 5.3 ft. (down)

Set - 16" Fir N.46°W., 30.8 ft.

22" Cedar West 11.5 ft.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13224)

The sec. cor. of secs. 27 & 34, monumented with a basalt stone, 14x10x8" firmly set 6" in the ground, marked on the N face, from which the original BTs:

A cedar, 9" dia., bears N.56 1/2°W., 16 lks., with a healed blaze. (Record bearing, N.54°W.)

A down hemlock, 12" dia., bears S.78°E., 6 lks., with no marks remaining on decayed blaze. (Record bearing & distance, S.21°E., 8 lks.) This tree has slid out of position with no remaining evidence of the stump hole. and bearing trees marked by Lecklider in 1960

A down fir, 15" dia., bears N.46°W., 46 1/2 lks., with scribe marks S27 RE4079 BT visible on unhealed double blaze.

A cedar, 18" dia., bears West, 17 lks., with scribe marks S34 RE4079 BT visible on unhealed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 25" in the ground with brass cap marked

1/4 S 27

S 34

T25S R2W

1962

No suitable tree available in sec. 34

Deposit the orig. corner stone alongside the iron post.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford, & G. Steven Popken Cadastral Surveyors & Glenn S. Baughman, LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15123)

The ¼ sec. cor. of secs. 27 & 34, perpetuated & recorded by Lecklider, in 1960, and remonumented by Brooks, in 1962. with an iron post, 2½" dia., firmly set, protruding 6" above ground, alongside of which is the original basalt stone, 12x10x8" firmly set, mkd. ¼ on N face, with brass cap (properly) mkd.

from which a BT mkd. by Lecklider

A cedar, 22" dia., bears S.75°W., 17 lks. with fragmentary scribe marks visible on open blaze. and a new bearing tree

A fir, 17" dia., bears N.51½°W., 93½ lks., mkd. ¼ S27 BT.

BLM dependent resurvey by Brian S. Seibold, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1754, surveyed May 1995/July 1998 - (DCSO records Vol. 53 Page(s) 20458)

The ¼ sec. cor. of secs. 27 & 34, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap mkd.

¼ $\frac{S\ 27}{S\ 34}$

T25S R2W

1962

from which a BT mkd. by Lecklider

A cedar, 26" dia., bears S.75°W., 14½ lks., with healed blaze. (Record, 17 lks.)

and a BT mkd. by Berry, Wofford, Popken and Baughman

A hemlock, 23" dia., bears N.48°W., 93½ lks., with healed blaze. (Record, N.51½°W.)

Cor. is located S., 0.25 chs. dist. from a creek, 2 lks. wide, course N.35°W.

Ken Hoffine - Crew: Gary Angiolet & Ignacio Roman - 6/2017 - C.S. File 65/101-52

Found - 1962 BLM brass cap

24" hemlock bears N.48°W., 60.9 ft. (Record from 2000 BLM renewal N.48°E., 61.71 ft.) Healed face and BLM tag

34" Cedar bears S.74¾°W., 9.6 ft. (Record from 2000 BLM renewal S.75°W., 9.57 ft.) Healed face and BLM tag. continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New - 11" cedar bears N.55½°E., 19.4 ft. we scribe T25S
R2W ¼ S27 BT and tag tree

11" D.Fir bears S.77½°E., 51.4 ft. we scribe T25S
R2W ¼ S34 BT and tag tree

Note - We ran a random loop transit traverse beginning at
the NE corner of sec 34 along the north line of
sec 34, to the north ¼ corner corner of sec. 34,
we mkd property boundaries on true line between
corners. The north ¼ corner lies in wet area at
head of draw.