

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3623)

Set basalt stone 14x10x6", 10" in the ground for ¼ sec. cor. marked ¼ on N faces, from which

A chinquapin, 6" dia. bears S.12°E., 38 lks. mkd: ¼ S15 BT

A chinquapin, 6" dia. bears N.17°W., 32 lks. mkd: ¼ S10 BT

Douglas Co. Surveyors Office - B.B. Irving, Co. Surveyor - A.R. Evans, Deputy - Wit: Milo Godfrey, Les Kershner, J.I. Clinton - Feb. 1948 - C.S. File 39/169 & M 12-34

Found - Rock corner, identified on OBTs

New - 66" Fir, N.58°E., 20.0 ft.

6" Fir, S.46°E., 37.6 ft.

Fd. OK by G. McChesney, WEYCO - 2/11/1960 C.S. 53/112-13 - Added "W" nails & plates to Irving's BTs

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13228-9)

The ¼ sec. cor. of secs. 10 and 15, monumented with a basalt stone, 14x10x6" firmly set 6" in the ground, marked ¼ on the N face, from which the original bearing trees:

A chinquapin snag, 8" dia., bears N.17°W., 32 lks., with no marks remaining on decayed blaze.

A chinquapin snag, 7" dia. bears S.10°E., 38 lks. with no marks remaining on decayed blaze. (Rec bearing S.12°E.)

and bearing trees marked by Irving in 1958

A fir, 85" dia., bears N.68°W., 35 lks., mkd T25S R2W S10 CS BT, on bark.

A sawed fir stump, 11" dia., bears S.50°E., 58 lks., with a healed blaze on down trunk.

At the corner point

Set an iron post, 28" long, 2" dia., 24" in the ground, & in a mound of stone, 2 ft. base, to top, with brass cap mkd:

$$\frac{1}{4} \begin{array}{l} S 10 \\ S 15 \end{array}$$
T25S R2W
1962

from which new BTs

A chinquapin, 12" dia., bears N.30½°E., 63 lks., mkd: ¼ S10 BT.

A fir, 8" dia., bears S.3½°E., 59 lks., mkd: ¼ S15 BT.

Deposit the orig. corner stone alongside the iron post.

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Greg Lang, LS 2205 - For: Roseburg Res. & R. McKenzie -
Feb. 1992 - M114-57

Found - 1962 brass cap
72" fir bears approx. N.68°E., 23.3 ft. healed blaze
(rec. NW per BLM resurvey, rec NE per Irving ren)
Now 14" fir bears approx. S.3½°E., 39.3 ft. healed
face.