

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3625)

-----  
Set a fir post 3 ft. long 3" sq. 24" in the ground for ¼ sec. cor. marked ¼ S3 on N and S 10 on S faces, from which  
A fir, 5" dia., bears N.14°W., 21 lks., mkd: ¼ S3 BT.  
A maple, 6" dia., bears S.30°E., 13 lks., mkd: ¼ S10 BT.

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13347)

-----  
The ¼ sec. cor. of secs. 3 & 10, determined at rec dist from the original BTs:

A fir, 10" dia., bears N.14°W., 21 lks., blaze chopped open, scribe marks 4 S3 visible.  
A maple stump, 12" dia., bears S.20½°E., 13 lks., blaze healed. (Record bearing, S.30°E.)

At the corner point

Set an iron post, 36" long, 1" diam., 28" in the ground, with brass cap mkd.  
¼  $\frac{S \ 3}{S \ 10}$

from which 1951

A sugar pine, 22" dia., bears N.1°45'W., 56 lks., mkd. ¼ S3 BT.  
A hemlock, 8" dia., bears S.1°45'W., 86 lks. mkd. ¼ S10 BT

Fd. BC & 2 BTs by G. Lang, 2/1992 - M114-57

Mark Smalley, Roseburg Forest Products - Crew: Bill Olson & Mike Fromdahl - 4/22/2003 - C.S. File 65/45-28

-----  
Found - 1951 GLO brass cap properly marked.  
Maple cluster S.20½°E., 8.6 good condition.  
Fir stump N.14°W., 14.0 gone.  
New BTs- 6" Fir N.48°W., 35.0 ft. scribe "S3 BT"  
16" Fir S.48°E., 34.3 ft. scribe "S10 BT"  
14" Fir N.79°E., 28.1 ft. scribe "S3 BT"