

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 3; & 34, T24-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2869)

-----  
Set Cedar post 3 ft. long, 3" sq., 24" in ground for ¼ sec. cor. mkd. ¼ S. on N. faces, from which  
A Fir 30" dia., bears N.20°W., 39 lks. dist. mkd. ¼ S BT.  
A Fir 16" dia., bears S.89°W., 18 lks. dist. mkd. ¼ S BT.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13279)

-----  
"The intermediate corners along this line which were established by McQuinn formerly referred only to T. 24 S., R. 2 W. The purported retracement of the south boundary of sec. 31 and the reported establishment of closing corners on the boundary by Hezekiah Johnson in 1900 **having proved to be fictitious**, the McQuinn corners except for the south ¼ sec. cor. of sec.31 and the south ¼ sec. cor. of sec. 36, are changed in 1963 to corners of maximum control in order to provide a basis for Consent Decree "Civil No. 60-135, Oregon."

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner. This now becomes the ¼ sec. cor. of secs. 3 and 34.

Set an iron post, 36" long, 1" dia., 28" in the ground, with brass cap mkd:

¼  $\frac{S\ 34}{S\ 3}$   
1951

from which

A Fir 28" dia., bears N.48½°W., 81 lks. dist. mkd. ¼ S34 BT. (1951 BT)

A Fir 25" dia., bears S.48¼°W., 53 lks. dist. mkd. ¼ S3 BT. (1963 BT)

FD BC & 2 BTs, D. Edwards 5/2008 - M156-7