

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3605)

-----  
Set a basalt stone 16x10x10", 11" in the ground for ¼ sec. cor. marked ¼ on W face & raised a mound of stone 2 ft. base, 1½ ft. high W of cor. Pits impracticable.

G. Robert Lecklider - For: Evans Products Co. - Aug. 1960 - M19-40

-----  
Set by proportionate measurement  
Set - Steel tube with survey cap.  
18" fir N.35°W., 35.5 ft.  
18" Fir S.23°W., 13.6 ft.  
28" fir S.32°E., 59.3 ft.

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - 5/10/1974 - C.S. File 56/51-6

-----  
Found - Steel tube & survey cap mkd. "Property Corner" & 3 fir BTs as described by Lecklider in 1960.  
We found NO evidence of the purported visit by County Surveyors office crews to this corner in 1968 (did not type calls for fd orig. BTs - none was marked - JC 11/10/2004)  
This corner lies on a southwesterly slope in a dense growth of fir & vine maple.

BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford, & G. Steven Popken Cadastral Surveyors & Glenn Baughman, LS, contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Pages 15115)

-----  
The ¼ sec. cor. of sees. 34 & 35, re-established & recorded by Lecklider, in 1960 monumented with a steel tube, 3/4" dia., firmly set, protruding 6", above ground, from which bearing trees mkd. by Lecklider:  
A fir, 20" dia., bears N.35°W., 54 lks., with healed double blaze.  
A fir, 33" dia., bears S.32½°E., 90 lks., with healed double blaze.  
A fir, 24" dia., bears S.23°W., 21 lks. , with healed double blaze.

At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T25S R2W  
¼  
S 34|S 35  
1974

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new bearing trees  
A fir, 10" dia., bears N.73°E., 72 lks., mkd. ¼ S35 BT.  
A fir, 28" dia., bears S.40½°W., 38 lks., mkd. ¼ S34 BT.  
Deposit steel tube alongside iron post.

FD. & used on BLM dependent resurvey by Brian S. Seibold, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1754, surveyed May 1995/July 1998 - (DCSO records Vol. 53 Page(s) 20455-6)

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2919, surveyed May 2018/July 2020 - (DCSO records Vol. 59 Page(s) 23922)

-----  
The ¼ sec. cor. of secs. 34 and 35, monumented with an iron post, 2½" dia., firmly set, projecting 9" above ground (alongside of which is an iron post, 1/2" dia I firmly set projecting 12" above ground, with aluminum cap mkd. PROPERTY CORNER), with a brass cap (properly) mkd.  
from which the remains of the bearing trees mkd. by Lecklider PE No. 4079, in 1960, reported by Berry, Wofford, Popken, and Baughman in 1972-75  
A fir, 41" dia., bears S.32½°E., 59.4 ft., with a healed blaze.  
A fir stump, 32" dia., bears S.23°W., 13.9 ft., with a healed blaze.  
A decayed fir stump, 27" dia., bears N.35°W., 34.3 ft., with a healed blaze.  
and the remains of the bearing trees mkd. by Berry, Wofford, Popken, and Baughman in 1972-75  
A fir, 27" dia., bears N.73°E., 47.5 ft., with a healed blaze.  
A decayed fir stump, 33" dia., bears S.40½°W., 25.1 ft., with a healed blaze.  
and a new bearing tree  
A fir, 7" dia., bears S.63¼°W., 15.0 ft., mkd. ¼ S34 BT.  
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.  
NAD 1983 (2011)  
Lat: 43°21'02.32" N Long: 122°54'47.58" W