

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34 & 35

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3604)

-
- A point about 500 ft. below summit of ridge. Set a basalt stone 16x2x8", 11" in the ground for cor. of secs. 26, 27, 34 & 35 mkd with 1 notch on S & 2 notches on E edges, from which
 - A hemlock, 7" dia., bears N.15°E., 14 lks., mkd: T25S R2W S26 BT.
 - A hemlock, 9" dia., bears S.85°E., 26 lks., mkd: T25S R2W S35 BT.
 - A hemlock, 6" dia., bears S.22°W., 43 lks., mkd: T25S R2W S34 BT.
 - A hemlock, 5" dia., bears N.59°W., 35 lks., mkd: T25S R2W S27 BT.

G. Robert Lecklider - For: Evans Products Co. - Aug. 1960 - M19-40

-
- Found - Corner stone
 - 10" Hem. N.15°E., 9.2 ft.
 - 12" Hem. S.85°E., 17.2 ft.
 - 10" Hem. S.22°W., 28.4 ft.
 - 16" Hem. N.59°W., 23.1 ft.
 - Set - Steel tube with survey cap
 - 14" Hem. N.89°E., 33.6 ft.
 - 10" Hem. N.52°W., 30.2 ft.
 - 10" Hem. S.72°W., 29.0 ft.
 - 12" Hem. S.45°E., 30.0 ft.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13220-1)

The cor. of secs. 26, 27, 34 & 35, monumented with a basalt stone, 16x12x8", firmly set 7" in the ground, marked with 1 notch on the S. & 2 notches on the E. edge, and perpetuated & recorded by G. Robert Lecklider in 1960, with a steel tube, 36" long, 3/4" dia., topped with an unmarked aluminum cap, firmly set 24" in the ground, alongside the corner stone, from which the original bearing trees:

- A down hemlock, 11" dia., bears N.13°E., 14 lks., with a healed blaze. (Record bearing, N.15°E.)
- A hemlock, 18" dia., bears East, 26 lks., with a healed blaze. (Record bearing, S.85°E.)
- A hemlock, 10" dia., bears S.14½°W., 43 lks. with a healed blaze. (Record bearing and distance, N.59°W., 35 lks.)

and trees marked by Lecklider
continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

- A hemlock, 15" dia., bears N.82°E., 51 lks., with scribe marks S26 RE4079 BT visible on unhealed double blaze.
- A down hemlock, 16" dia., bears S.46°E., 40 lks., with scribe marks S35 RE4079 BT visible on an unhealed double blaze.
- A down hemlock, 10" dia., bears S.64°W., 44 lks., with scribe marks S34 RE4079 BT visible on an unhealed double blaze.
- A hemlock, 9" dia., bears N.57°W., 47 lks., with scribe marks S27 RE4079 BT visible on an unhealed double blaze.

At the corner point

Set an iron post, 28" long, 2" dia., 26" in the ground with brass cap marked

T25S R2W
S 27 | S 26
S 34 | S 35
 1962

Deposit the original corner stone and reset the steel tube alongside the iron post.

BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford, & G. Steven Popken Cadastral Surveyors & Glenn S. Baughman, LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15114-5)

The cor. of secs. 26, 27, 34, & 35, perpetuated & recorded by G. Robert Lecklider, in 1960, and remonumented by Brooks, in 1962, with an iron post, 2½" dia., firmly set, protruding 4" above ground, alongside of which is a steel tube, ¾" dia., firmly set, protruding 6" above ground, alongside of which is the orig. basalt stone, 16x12x8" firmly set mkd. with 1 notch on S. & 2 notches on E. face, with brass cap (properly) mkd. from which the remains of the original bearing trees

- A root hole, bears N.13°E., 14 lks., with a down hemlock, alongside. 12" dia., with healed blaze.
- A hemlock snag, 20" diam., bears S.85°E., 26 lks., with healed blaze. (Record, East)
- A root hole, bears N.59°W., 32 lks., with a down hemlock alongside, 14" dia., with fragmentary scribe marks visible on open blaze. (Record, N.65°W.)

and the remains of bearing trees mkd. by Lecklider

- A hemlock snag, 14" dia., bears N.89°E., 51 lks with fragmentary scribe marks visible on open blaze.
- A root hole, bears S.46°E., 45 lks., with a down hemlock alongside, 12" dia., no marks visible.
- A root hole, bears S.72°W., 44 lks., with a down hemlock alongside, 12" dia., no marks visible. cont. next pg

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34 & 35

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A hemlock, 11" dia., bears N.50°W., 47 lks., with scribe marks RE4079 BT visible on open double blaze.
and new BTs
A hemlock, 10" dia., bears N.43½°E., 66½ lks., mkd: T25S R2W S26 BT.
A hemlock, 16" dia., bears S.60½°E., 72 lks., mkd: T25S R2W S35 BT.

Ken Hoffine - Crew: Gary Angiolet & Ignacio Roman - 6/2017 - C.S. File 65/101-53

Found - 1962 BLM Brass cap
20" hemlock bears N.44°E., 44.0 ft. (Record from 1962 BLM renewal N.43½°E., 43.89 ft.) healed face and BLM tag
24" hemlock bears S.60½°E., 45.35 ft. (Record from 1962 BLM renewal S.60½°E., 47.52 ft.) Healed face and BLM tag
New - 18" Hemlock bears N.1¼°E., 11.0 ft. We scribe T25S R2W S26 BT and tag tree
14" D.Fir bears S.48¾°W., 38.6 ft. We scribe T25S R2W S34 BT and tag tree
Note - We ran a random loop transit traverse beginning at the NE corner of section 34 along the north line of section 34, to the north ¼ corner corner of section 34, we marked property boundaries on true line between corners. Corner lies on steep north facing slope and is approx. 0.2 feet above ground level.