

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3612)

Set a dogwood post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S10 on W & S 11 on E faces, from which
A fir, 40" dia., bears N.52°W., 40 lks., mkd: 1/4 S10 BT.
A cedar, 13" dia., bears S.64°E., 54 lks., mkd: 1/4 S11 BT.

Glen McChesney, Weyerhaeuser Co. - 3/1960 - C.S. 53/112-12

Found - 2 orig. BTs
New - 36" Cedar, S.2°E., 14.0 ft. "W" nail & plate.
48" Fir, N.53°W., 25.8 ft. added "W" nail & plate, OBT

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13223)

The 1/4 sec. cor. of secs. 10 & 11, determined at record bearing & distance from the original BTs:
A cedar, 18" dia., bears S.64°E., 54 lks., with no marks remaining on a burned-out blaze.
A fir, 55" dia., bears N.52°W., 40 lks., with a healed blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground with brass cap marked

1/4
S 10 | S 11
T25S R2W
1962

from which a new bearing tree
A hemlock 9" dia., bears S.24 1/2°E., 35 lks. marked 1/4 S11 BT

Nick Juliano - For: Weyerhaeuser - 12/1976 - M62-74

Found - BLM brass cap 1962
12" Hem, S.24 1/2°E., 23.1', closed face.
38" Cedar, S.2°E., 24.0', closed face & W.CO. RP
42" Fir, S.53°W., 25.8', closed face & W.CO. RP

Fd. Ok by G. Lang, 2/1992 - M114-57
Fd. Ok by S. Ness, 10/1995 - M123-3 A&B

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed May 2001/June 2002- (DCSO rec. Vol. 54 Page(s) 20926)

The ¼ sec. cor. of secs. 10 & 11, monumented with an iron post, 2½" dia., firmly set, projecting 1" above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees
A cedar stump, 18" dia., bears S.68¾°E., 35.6 ft., with no marks visible. (Record, S.64°E.)

A fir stump, 54" dia., bears N.56°W., 25.6 ft., with healed blaze. (Record, N.52°W., 26.4 ft.)

and a bearing tree mkd. by Brooks
A hemlock, 18" dia., bears S.29½°E., 23.1 ft., with healed blaze. (Record, S.24½°E.)

and BT mkd by person(s) unknown, reported by Juliano, in 1977
A cedar, 41" dia. bears S.9¾°E. 16.6 ft. with healed blaze

Mark Smalley - For: Roseburg Resources - May 2003 - C.S. File 65/48-6

Found - 1962 Steel pipe & brass cap (properly marked)
17" Hemlock S.24½°E., 23.1' no face.

40" Cedar S.64°E., 35.6' found face chopped into.
57" Fir stump N.52°W. 26.4' fd. face chopped into

New - 15" Hemlock S.18°W., 11.6' scribed "¼ S BT"