

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3614-5)

Point on steep mountain side, sloping E
Set a basalt stone 16x8x6", 11" in the ground for ¼ sec. cor. marked ¼ on W face from which
A cedar, 16" dia., bears N.81°E., 12 lks., mkd: ¼ S2 BT.
A dogwood, 6" dia., bears S.36°W., 15 lks., mkd: ¼ S3 BT.

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13346)

The sec. cor. of secs. 2 & 3, monumented with a basalt stone, 12x10x8" firmly set marked ¼ on W face from which the OBTs
A cedar, 18" dia., bears N.81¼°E., 14 lks., blaze rotted, scribe marks ¼ 2 visible. (Rec: bears N.81°E., 12 lks.)
A dogwood, 7" dia., bears S.34°W., 14 lks., blaze rotted. (Record: bears S.36°W., 15 lks.)
At the corner point
Set an iron post, 36" long, 1" dia., 28" in the ground, with brass cap mkd. ¼
S 3|S 2
1951
from which
A hemlock, 24" dia., bears N.63°E., 23 lks., mkd. ¼ S2 BT.
A hemlock, 12" dia., bears S.55°45'W., 60 lks., mkd. ¼ S3 BT.

Fd. Ok by N. Juliano, 12/1976 - C.S. File 58/130-1