

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T24-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2868-69)

Set post 4 ft. long, 4" sq., 24" in ground for cor. to secs. 2, 3, 34 and 35, mkd. T24S S35 on NE.; R2W S2 on SE.; T25S S3 on SW.; and S34 on NW. faces with 4 notches on W. and 2 notches on E. edges, from which

A Fir 20" dia., bears N.32°E., 26 lks. dist. mkd. T24S R2W S35 BT.

A Fir 10" dia., bears S.71°E., 43 lks. dist. mkd. T25S R2W S2 BT.

A Maple 20" dia., bears S.82°W., 39 lks. dist. mkd. T25S R2W S3 BT.

A Fir 12" dia., bears N.32°W., 28 lks. dist. mkd. T24S R2W S34 BT.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13278-79)

"The intermediate corners along this line which were established by McQuinn formerly referred only to T. 24 S., R. 2 W. The purported retracement of the south boundary of sec. 31 and the reported establishment of closing corners on the boundary by Hezekiah Johnson in 1900 having proved to be fictitious, the McQuinn corners except for the south ¼ sec. cor. of sec.31 and the south ¼ sec. cor. of sec. 36, are changed in 1963 to corners of maximum control in order to provide a basis for Consent Decree "Civil No. 60-135, Oregon." (Hezekiah Johnson fictitious corner on Page 3614)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner. This now becomes the cor. of secs. 2, 3, 34 and 35.

Set an iron post, 36" long, 2" dia., 28" in the ground, with brass cap mkd:

T 24 S	R 2 W
S 34	S 35
S 3	S 2
T 25 S	
1951	

from which

A Cedar 15" dia., bears N.45½°E., 92 lks. dist. mkd. T24S R2W S35 BT. (1963 BT)

A Cedar 37" dia., bears S.38°E., 32 lks. dist. mkd. T25S R2W S2 BT. (1963 BT)

(Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T24-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Cedar 35" dia., bears S.46¼°W., 36 lks. dist. mkd. T25S
R2W S3 BT. (1963 BT)
A Cedar 18" dia., bears N.57°W., 77 lks. dist. mkd. T24S
R2W S34 BT. (1951 BT)

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 5/2015 - C.S.
File 65/89-2

Found - GLO brass cap (properly mkd)
29" Cedar N.45½°E., 60.7 ft. good scar.
40" Cedar S.38°E., 21.1 ft. good scar.
40" Cedar S.46°W., (rec. 46¼) 23.8 ft. good scar.
31" Cedar N.57°W., 50.8 ft. good scar.
New - NE corner Tract 38 bears N.16°E., 29.9 ft.
Note - Hand held Lat: 43°26.209 Long: 122°55.936
Compass decl. 15½°E.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 5/25/2022 (Filed 7/20/2022) - C.S. File 67/52-40

Found - 2½" GLO brass cap (properly mkd) on 1¾" I.D. I.Pipe
projecting 12".
BLM BTs
Burnt-sawn 30"x3 ft. Cedar stump N.45½°E., 60.7 ft.
good scar.
Burnt 40" Cedar S.38°E., 21.4 ft. (Rec. 21.1 ft.)
add 3½" PK nail, right side center.
Burnt broken 40"x10' Cedar snag S.46½°W., 23.4 ft.
(rec. S.46°W., 23.8 ft)
Burnt 32" Cedar N.57°W., 50.8 ft. good scar.
NE cor. Tract 38 bears N.16°E., 29.9 ft.
New - Burnt 20" Hemlock N.86°E., 9.2 ft., 3½" PK right
side center, not blazed or scribed.
Metal lath SSE 1½ ft.
Note - Hand held Lat: 43°26.209N Long: 122°55.936W
Compass decl. 14½°E.
Area burnt 9/2020
See sketch in file.
GPS location for 500100 is from 500101 N.16°E., 29.9 ft.