

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 520200

PRIMARY CORNER DESCRIPTION W 1/16 Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Nick Juliano - For: Weyerhaeuser Co. - 10/1973 - M51-27

Set - (2"x30" iron pipe with brass cap per map)
A RR Spike in a 11" Fir, N.22°E., 3.5'
A RR spike in a 14" Fir, S.1°W., 10.4'

BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford,
& G. Steven Popken Cadastral Surveyors & Glenn S. Baughman,
LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854,
surveyed July 1972/Oct. 1975 - (DCS0 records Vol 36 Pg 15117)

The W 1/16 sec. cor. of secs. 26 and 35, established by
Juliano, Registered Logging Engineer, in 1973, monumented
with an iron post, 2" dia., firmly set, protruding 6" above
ground, with brass cap mkd.

T25S R2W
W 1/16 $\frac{S\ 26}{S\ 35}$
1973

from which bearing trees mkd. by Juliano
A fir, 13" dia., bears N.21½°E., 5½ lks., with a railroad
spike driven into base.
A fir, 18" dia., bears S.1°W., 16 lks., with a railroad
spike driven into base.
and new bearing trees
A fir, 15" dia. bears N.33½°E., 33½ lks. mkd W 1/16 S26 BT
A fir, 15" dia., bears S.23½°W., 28 lks. mkd W 1/16 S35 BT

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 12/7/2021 (Filed 4/11/2022) - C.S. File 67/51-38

Found - 2½" brass cap on I. Pipe (properly mkd)
15"x12' fir snag N.21½°E., 3.6 ft to spike
20"x7' burned fir snag S.1°W. 10.3 to spike rec 10.6
10"x6 burnt stump N.33½°E., 22.1 ft.
19" burnt Fir snag, S.23½°W., 18.5 ft., healed scar.
New - 5/8" IR inside 3/4" I.D. x 23" iron pipe in rough
mound of stone, bears S.60°E., 58.1 ft.
Burnt 8", dead, hemlock, healed HI-L0 blaze
S.85¼°W., 11.4 ft. June 2010 BLM tag.
9"x 6 ft burnt fir snag not blazed or scribed
S.36°E., 11.4'
21" burned dead D.Fir possible healed blaze N.80°W.,
2.3 ft.

Note - Area burnt 9/2020
Compass decl. 14½°E.
See sketch in file

Lat: 43°21'28.66" N Long: 122°54'30.23" W.