

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A hemlock, 21" dia., bears N.64°W., 7 lks., with scribe marks ¼ S26 CS BT visible on open double blaze.
A hemlock, 21" dia., bears S.25°W., 63½ lks., with scribe marks ¼ S35 CS BT visible on open double blaze.
and a reference monument
An iron post, 28" long, 2½" dia., set 24" in the ground, for a reference monument, bears S.11½°W., 15 lks., with brass cap mkd. T25S R2W S35 RM 1974, and an arrow pointing to the corner.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22800-1

The ¼ sec. cor. of secs. 26 and 35, perpetuated by the Douglas County Surveyors Office in 1967, occupied by the original cor. tree, a hemlock snag, 7" dia., with no marks remaining, alongside of which is an iron post, 2" dia., firmly set, projecting 11" above the ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T25S ¼ S26 S35 R2W 1967 from which the original bearing trees
A hemlock, 12" dia., bears S.8°E., 16.5 ft., with scribe marks 4S visible on an open blaze.
A hemlock, 36" dia., bears N.10°W., 2.0 ft., with scribe marks 4S visible on an open blaze.
and BTs mkd. by the Douglas County Surveyor's Office
A hemlock, 29" dia., bears S.25°W., 41.9 ft., with a healed blaze.
A hemlock, 23" dia., bears N.64°W., 4.6 ft., with a healed blaze.
and a reference monument established by Berry, Popken, Wofford, and Baughman
An iron post, 2½" dia., firmly set, projecting 3" above the ground, bears S.10°11'55" W., 9.89 ft., with brass cap mkd. T25S R2W S35 RM 1974 and an arrow pointing to the cor.