

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 540240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Nick Juliano, Triangle Eng. - For: Weyerhaeuser - 10/1973 - M 51-27

Set - 2"x30" IP with a brass cap.
A RR spike in a 42" Fir, S.55°E., 7.8 ft.
A RR spike in a 48" Fir, N.23°W., 19.7 ft.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22801-2

The center ¼ sec. cor. of sec. 26, established by Juliano, in 1973, and is accepted as the cor., monumented with an iron post, 2" dia., firmly set, projecting 6" above the ground, with brass cap mkd.
T25S R2W
S 26
C ¼
1973

from which the remains of bearing trees mkd. by Juliano
A sawed fir stump, 47" dia., bears S.53½°E., 10.2 ft., with a railroad spike in the face and no marks visible.
A sawed fir stump, 57" dia., bears N.21½°W., 22.0 ft., with a railroad spike in the face and no marks visible.
and new bearing trees
A fir, 11" dia., bears N.37°E., 2.0 ft., mkd. C ¼ S26 BT.
A fir, 11" dia., bears N.61¼°W., 24.7 ft., mkd C ¼ S26 BT.