

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3609)

Set a basalt stone 14x10x6", 10" in the ground for ¼ sec. cor. marked ¼ on N face, from which
A hemlock, 10" dia., bears N.42°W., 18 lks., mkd: ¼ S14 BT
A hemlock, 9" dia., bears S.3°W., 32 lks., mkd: ¼ S23 BT.

Glen McChesney, Wey Co. - 8/17/1959 - C.S. File 53/112-23

Found - Orig. stone mkd: ¼
12" hemlock, face scars, N.44°W., 11.8'
16" hemlock, face scars, S.4°W., 21.1', added "W" nail & plate.
New - 46" hemlock, N.39°W., 18.8 ft., "W" nail & plate.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13222)

The sec. cor. of secs. 14 & 23, monumented with a basalt stone, 14x10x6", firmly set 10", in the ground, marked on the N face, from which the original bearing trees:
A hemlock, 14" dia., bears N.42°W., 18 lks., with scribe mark S visible on partly opened blaze.
A hemlock, 20" dia. bears S.3°W. 32 lks. with healed blaze
At the corner point
Set an iron post, 28" long, 2½" dia., 26" in the ground with brass cap marked
¼ $\frac{S\ 14}{S\ 23}$
T25S R2W
1962
from which a new bearing tree
A hemlock 15" dia., bears N.46°E., 32 lks., marked S14 BT.
Deposit the original corner stone alongside and break a clear glass bottle at base of the iron post.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed May 2001/June 2002- (DCSO rec. Vol. 54 Page(s) 20923-4)

The ¼ sec. cor. of secs. 14 & 23, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with orig. stone buried alongside, with brass cap (properly) mkd. from which the remains of the original bearing trees
A roothole, bears S.3°W., 21.1 ft., with fallen hemlock trunk lying alongside, with healed blaze.
continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A roothole, bears N.42°W., 11.9 ft.
and remains of the bearing tree mkd. by Brooks
A roothole, bears N.46°E., 21.1 ft.
and new bearing trees
A cedar, 27" dia., bears S.66¾°W., 39.3 ft., mkd. ¼ S23 BT
A hemlock, 12" dia. bears N.13½°W., 53.5 ft. mkd. ¼ S14 BT
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center, unless otherwise
described in the corner description