

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3611)

-----  
Set a basalt stone 20x8x5", 15" in the ground for 1/4 sec. cor. marked 1/4 on N face, from which  
A cedar, 14" dia., bears N.25°E., 10 lks., mkd: 1/4 S11 BT.  
A yew, 10" dia., bears S.31°E., 13 lks., mkd: 1/4 S14 BT.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13222)

-----  
The 1/4 sec. cor. of secs. 11 & 14, monumented with a basalt stone, 20x8x5", firmly set 15", in the ground, marked on the N. face, from which the only remaining original BT  
A cedar, 21" dia., bears N.4°W., 11 lks., with scribe mark 4 visible on an opened blaze. (Record bearing & dist. N.25°E., 10 lks.)  
and a bearing tree of which I have no record  
A hemlock, 10" dia., bears S.62°W., 26 lks., with scribe marks T25S R2W 1/4 S14 CS BT on unhealed double blase,  
At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap marked  
1/4  $\frac{S\ 11}{S\ 14}$   
T25S R2W  
1962  
from which a new bearing tree  
A cedar, 5" dia., bears N.8°E., 34 lks., marked 1/4 S11 BT.  
Deposit the original corner stone alongside the iron post.

Glen McChesney, Weyerhaeuser Co. - 11/2/1970 - C.S. File 53/112-20

-----  
Found - 1962 brass cap with stone alongside  
22" cedar, scribing visible, N.4°W., 7.3 ft. (OBT)  
10" hemlock, scribing visible, S.65°W., 17.2 ft. - unknown record  
6" cedar, scribing visible, N.8°E., 22.4 ft. (OBT)  
New - 40" Fir, N.44°W., 6.1 ft., "W" nail & plate.  
38" Fir, S.81°E., 24.8 ft., "W" nail & plate.

Steven Ness - For: Weyerhaeuser - 10/1995 - M123-3 A&B

-----  
Found - 3 1/4" BLM brass cap on 2 1/2" iron post.  
38" D.Fir stump. S.81°55'E., 26.3 to center. 24.94 to "W" nail. "W" nail is in small low blaze. (S.81°E., 24.8) continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Remains of hemlock windfall. S.67°04'W., 15.2 measure to root hole. (S.62°W., 17.2)  
44" D.Fir. N.43°07'W., 7.5 small low blaze healed. (N.44°W., 6.1 to "W" nail)  
24 W.R. Cedar N.8°09'W., 7.2. no face visible. (N.4°W. 7.3)  
11 W.R. Cedar N.6°07'E., 22.9' face healed. (N.8°E., 22.4)

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1979, surveyed May 2001/June 2002- (DCSO rec. Vol. 54 Page(s) 20935-6)

-----  
The ¼ sec. cor. of secs 11 & 14, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3" above the ground, with brass cap (properly) mkd. from which the remains of an original bearing tree  
A cedar snag, 25" dia., bears N.10¼°W., 7.2 ft., with healed blaze. (Record, N.4°W.)  
and remains of a BT mkd. by person(s) unknown, reported by Brooks  
A roothole, bears S.62°W., 17.2 ft. and a bearing tree mkd. by Brooks  
A cedar, 13" dia., bears N.5¼°E., 22.4 ft., with healed blaze. (Record, N.8°E.)  
and the remains of bearing trees mkd. by person(s) unknown, reported by Ness, in 1995  
A fir, 42" dia., bears N.46°W., 7.1 ft., with cruiser marks visible in the bark.  
A sawed fir stump, 38" dia., bears S.82°E., 26.2 ft., with healed blaze.  
and new bearing tree  
A hemlock, 9" dia., bears S.21¾°E., 10.8 ft. mkd. ¼ S14 BT  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description