

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 2; & 35, T24-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2868)

-----  
Set post 3 ft. long, 3" sq., 24" in ground for ¼ sec. cor. mkd. ¼ S on N. face, from which  
A Maple 20" dia., bears N.13°W., 25 lks. dist. mkd. ¼ S BT  
A Fir 40" dia., bears S.16°E., 38 lks. dist. mkd. ¼ S BT.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13278)

-----  
"The intermediate corners along this line which were established by McQuinn formerly referred only to T. 24 S., R. 2 W. The purported retracement of the south boundary of sec. 31 and the reported establishment of closing corners on the boundary by Hezekiah Johnson in 1900 having proved to be fictitious, the McQuinn corners except for the south ¼ sec. cor. of sec.31 and the south ¼ sec. cor. of sec. 36, are changed in 1963 to corners of maximum control in order to provide a basis for Consent Decree "Civil No. 60-135, Oregon."

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner. This now becomes the ¼ sec. cor. of secs. 2 and 35.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼  $\frac{S\ 35}{S\ 2}$   
1951

from which bearing trees mkd. in 1963:

A Hemlock 11" dia., bears N.33¼°E., 101 lks. dist. mkd. ¼ S35 BT.

A Fir 11" dia., bears S.19 3/4°W., 82 lks. dist. mkd. ¼ S2 BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 8/2/2023 - C.S. File 67/57-17

-----  
Reported as not found  
GPS location falls in a large logged flat with new road construction. Searched with multiple GPS ties and found no evidence.