

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 542100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only, T26-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 9 Page(s) 3580)

-----  
Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which  
A Chinquapin 8" dia., bears N.60°E., 60 lks. mkd. ¼ S BT.  
A Fir 4" dia., bears S.70°W., 38 lks. dist. mkd. ¼ S BT.

GL0 survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4269 & 4273)

-----  
(Page 4269) Searched diligently but could find none of the markings of the ¼ sec. cor. Set temp ¼ sec. cor. for sec. 2 (Page 4273) Set basalt stone 14x12x8", 9" in ground for ¼ sec cor. on N line of sec 2 only, mkd ¼ on S face; from which  
A Fir 12" dia., bears S.60°E., 34 lks. dist. mkd. ¼ S2 BT.  
A Fir 14" dia., bears S.44°E., 42 lks. dist. mkd. ¼ S2 BT.  
Cougar Peak bears S.7°30'W.

Survey by G. Robert Lecklider - For: Mrs. Carl A. Messing - July 6, 1959 - M 11-31

-----  
Found - Corner stone.  
32" Fir, S.60°E., 34 lks.  
32" Fir, S.44°E., 42 lks., rescribed.  
New BT - 5" Fir, S.40°E., 5.7 ft.

Ed Monrean - For: Roseburg Resources - April 2004 - M144-47 & C.S. File 65/49-34F

-----  
Found - 14"x12"x8" stone marked with "¼ on South face with tack in top.  
36" (32") fir with double healed faces, bears S.46°E., (S.60°E.) 22.4 ft.  
37" (32") fir with visible bark scribe "¼ S2" bears S.44°E., 27.7 ft.  
5" fir with double healed faces, bears S.30°E., (S.40°E.) 5.7 ft.  
Set - 5/8"x30" iron rod with a 2½" alum. cap, 0.4 ft. above grade with collar of small stones. Cap marked: ROSEBURG RESOURCES COMPANY

T25S R2W  
¼ S 2  
T26S R2W  
LS 1830  
2004

continued next page

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

New -	<p>Fd. stone set approx. 0.5 ft. North of alum. cap. The tack on top of the fd. stone was tied for coordinate value. The fd. stone was then moved &amp; the iron rod set in its place using the stakeout program in "TDS" data collector survey program.</p> <p>A D.Fir 9" dia., bears S.61°W., 27.1 ft., face scribed "T26S R2W S2 BT"</p> <p>A D.Fir 18" dia., bears N.1°W., 25.0 ft., face scribed "T25S R2W BT"</p>
	<p>BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22784-5</p> <p>-----</p> <p>The ¼ sec. cor. of sec. 2 only, T26S R2W perpetuated by Lecklider, in 1959, further perpetuated by Monrean, in 2004, monumented with an iron rod, 5/8" dia., firmly set, projecting 6" above the ground, (alongside of which is the original stone, 14x12", projecting 8" above the ground, with no marks visible), with aluminum cap (properly) mkd. from which the remains of bearing trees mkd. by Collier</p> <p>A fir, 48" dia., bears S.52¼°E., 22.4 ft., with a healed double blaze. (Record, S.60°E.)</p> <p>A fir, 39" dia., bears S.44°E., 27.7 ft., with scribe marks ¼ S2 visible on the bark.</p> <p>and a bearing tree mkd. by Lecklider</p> <p>A fir, 7" dia., bears S.34¼°E., 5.6 ft., with a healed double blaze.</p> <p>and bearing trees mkd. by Monrean</p> <p>A fir, 10" dia., bears S.55¾°W., 27.0 ft., with a healed blaze.</p> <p>A fir, 21" dia., bears N.6½°W., 25.0 ft., with a healed blaze.</p>
	<p>BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24069)</p> <p>-----</p> <p>The ¼ sec. cor. of sec. 2 only, on the N. bdy. of the Tp., reported by Skeesick in 2010-11, monumented with an iron rod, 5/8" dia., firmly set, projecting 6" above ground, firmly set, projecting, 8" above the ground, mkd. ¼ on the S. face), with an aluminum cap mkd. ROSEBURG RESOURCES T25S R2W ¼ S2 T26S R2W LS1830 2004 COMPANY, from which the bearing trees reported by Skeesick</p> <p>A fir, 48" dia., bears S.52¼° E., 22.4 ft., with a healed double blaze.</p> <p>Continued next page</p>

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 542100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only, T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 39" dia., bears S.44°E., 27.7 ft., with scribe marks  $\frac{1}{4}$  S2 visible on bark.

A fir, 7" dia., bears S.34 $\frac{1}{4}$ °E., 5.6 ft., with a healed double blaze.

A fir, 10" dia., bears S.55 $\frac{3}{4}$ °W., 27.0 ft., with a healed blaze.

A fir, 21" dia., bears N.6 $\frac{1}{2}$ °W., 25.0 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground, directly over the iron rod, with brass cap mkd.

T 25 S R 2 W

$\frac{1}{4}$  S 2

T 26 S R 2 W

2019

The basalt stone, 14x12x8" established by Collier in 1913-14, mkd.  $\frac{1}{4}$  on south face, was found set alongside the cor. Bury the stone alongside the cor.

Note: The cor. was incorrectly identified as an original cor. on the Skeesick plat.