

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION C C of secs. 35 & 36 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 9 Page(s) 3593-94)

At point of intersection, I set a basalt stone 16x11x8", 11" in the ground for closing cor. of secs. 35 and 36, marked CC with 1 notch on E & 5 notches on W edges, from which
A Maple 4" dia., bears N.18°E., 47 lks. dist. mkd. T25S R2W S36 BT.
A Hemlock 6" dia., bears N.72°W., 65 lks. dist. mkd. T25S R2W S35 BT.

GLO survey by Charles M Collier, under instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4269)

Searched for closing cor. of secs. 35 and 36, but could find no trace of it.

Survey by Les Roberts - For: Weyerhaeuser Co. - Oct. 1977 - M 67-61

Set 5/8" x 42" Rebar, from which
10" Fir N.20°E., 8.2 ft. to R.R. spike.
18" Fir N.42°W., 11.9 ft. to R.R. spike.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22784

The closing cor. of secs. 35 and 36 only, on the S. bdy. of the Tp., reestablished by Roberts, and is accepted as a careful and faithful reestablishment of the cor., monumented with an iron rod, 5/8" dia., firmly set, projecting 5" above the ground, from which bearing trees mkd. by Roberts
A fir, 20" dia., bears N.23°E., 8.8 ft., with no marks visible.
A fir, 25" dia., bears N.44°W., 12.4 ft., with no marks visible.

At the corner point
Drive an aluminum cap onto the iron rod, mkd.

C C
T25S R2W
S 35|S 36
S 2
T26S R2W
2010

Deposit a magnet in a white plastic case alongside the iron rod.