

PRIMARY CORNER DESCRIPTION W C 1/4 Cor. Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3594)

Set basalt stone 16x8x7", 11" in the ground for ¼ sec. cor. between secs. 35 & 36 marked ¼ on W faces, from which
A fir, 5" dia., bears S.81°E., 45 lks., mkd: ¼ S36 BT.
A hemlock, 4" dia., bears N.24°W., 23 lks., mkd: ¼ S35 BT.

Les Roberts - For: Weyerhaeuser Co. - Oct. 1977 - M67-61

Set - 5/8"x42" rebar in large mound of stone N.1°10¼'W., 44.0 ft. from point for ¼ corner.
36" Fir, bears N.10°E., 14.3 ft. to RR spike.
18" Fir, bears S.35°W., 31.0 ft. to RR spike.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22792-3

N.1°10'13"W., 2535.86 ft. (from CC Secs 35 & 36)
Point for the ¼ sec. cor. of secs. 35 & 36, determined at proportionate; there is no remaining evidence of the original cor.

Drive an aluminum rod, 36" long, 3/4" dia., 33" in the ground, with aluminum cap mkd. T25S R2W

¼
S 35|S 36
2010

from which

An ash, 13" dia., bears S.45½°E., 10.7 ft., mkd. ¼ S36 BT, with Mag Nail driven at the base on left side center.

A rock face bears S.79½°W., 2.8 ft., mkd. X BO.

Deposit a magnet in a white plastic case alongside the aluminum rod.

2579.82 ft

A point established by Roberts, in 1977, and is accepted as witness cor. for the ¼ sec. cor. of secs. 35 and 36, monumented with an iron rod, 5/8" dia., firmly, projecting 10" above a collar of stone, 1½ ft. base, from which the remains of bearing trees mkd. by Roberts

A sawed fir stump, 40" dia., bears N.11¼°E., 15.5 ft., with a railroad spike in the face and no marks visible.

A fir, 29" dia., bears S.34½°W., 31.4 ft., with a railroad spike in the face and no marks visible.