

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor Secs 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 47" dia., bears N.23°E., 38.9 ft., with a healed double blaze.
A sawed fir stump, 33" dia., bears S.70°E., 51.5 ft., with a healed double blaze.
A fir, 33" dia., bears S.29¼°W., 83.7 ft., with a healed double blaze. (Record, S.31°W., 85.5 ft.)
A fir, 78" dia., bears N.40°W., 28.4 ft., with a healed double blaze.
and a new bearing tree
A fir, 9" dia. bears S.43½°E., 9.2 ft mkd. T25S R2W S36 BT
NAD 1983 (CORS 96)
Latitude: 43°21'28.18" N. Longitude: 122°53'36.77" W.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 6/5/2023 - C.S. File 67/56-30

Found - ¾" BLM brass cap (properly mkd) up 3" in rough mound of stone.
Burned, dead 50" Fir snag N.22°E., 39.3 ft. (rec. N.23°E., 38.9 ft.) add ¾" mag nail right side center.
Burnt, sawed 34"x5 ft. fir stump S.70°E., 51.2 ft. (rec. 51.5 ft) add ¾" mag nail top center.
Burned, sawn 39"x2 ft. fir stump S.31°W., 83.7 ft. (rec. S.29¼°W.) add ¾" mag nail top center.
Burnt, sawn 59"x5 ft. fir stump N.40°W., 28.7 ft. (rec 28.4 ft) add ¾" mag nail right side center.
A Fir, burned broken off shattered to the ground level S.43½°E., 9.2 ft.
Alum post, south 1.5 ft. and on east edge.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Corner is approx. 130 ft. south of and 80' below gravel road on moderate S.E. slope
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
191487.293 N 281004.427 E