

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 600220

PRIMARY CORNER DESCRIPTION S 1/16 Secs. 25 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford, & G. Steven Popken Cadastral Surveyors & Glenn S. Baughman, LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct. 1975 - (DCS0 records Vol 36 Pg 15113)

Point for the S 1/16 sec. cor. of secs. 25 and 26.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.
S 1/16
S 26|S 25
1974

from which
A hemlock, 16" dia., bears N.47°E., 84 lks., mkd: S1/16 S25 BT.
A hemlock, 18" dia., bears S.73½°W., 37 lks., mkd: S1/16 S26 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/3/1992 - C.S. File 64/23-13

Found - 3¾ BLM Brass cap on a 2½" O.D. iron pipe protrudes 13" above ground. (Properly mkd) (1974 BLM) Cap is firmly set & plumb. Marks on top of cap face Southeast not north, we did not reset BC/IP.
18" now 14" dia., 3½" high hemlock stump with gal. steel cap, scribing visible on an unhealed single blaze "S 1/16 S26 BT", bears S.73½°W., 24.4 ft. (agrees with rec) 1974 BLM
16" now 15" dia., 3 ft. high hemlock stump with gal. steel cap, scribing visible on an unhealed single blaze "S 1/ 25 BT" bears N.48½°E., 55.4 ft. (Rec. N.47°E., 55.4 ft.) 1974 BLM
New - 22" dia., G.Fir double blazed & scribed "S1/16 S26 CS BT" bears S.44°W., 79.0 ft.
22" dia., Hemlock double blazed & scribed "S 1/16 S26 CS BT" bears S.16°W., 96.1 ft.