

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias	Description

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3595)

Set basalt stone 16x8x7", 11" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A fir, 36" dia., bears S.59°E., 23 lks., mkd: ¼ S25 BT.

A hemlock, 30" dia., bears S.35°W., 39 lks., mkd: ¼ S26 BT

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13216)

The ¼ sec. cor. of secs. 25 & 26, monumented with a basalt stone, 16x8x7", firmly set 10" in the ground, marked ¼ on the W face, from which the orig. BTs:

A fir, 40" dia., bears S.59°E., 29 lks., with healed blaze. (Rec. dist. 23 lks.)

A hemlock, 28" dia., bears S.35°W., 39 lks., with scribe marks ¼ S26 visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked:

¼
S 26|S 25
T25S R2W
1962

from which a new BT

A cedar, 9" dia., bears N.33½°W., 10½ lks., mkd: ¼ S26 BT.

Deposit the orig. corner stone alongside the iron post.

Fd & used on BLM dependent resurvey by Daniel L Berry, Harvey Wofford, & G Steven Popken Cad. Surveyors & Glenn Baughman, LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct 1975 - (DCSO records Vol. 36 Pg 15113)

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22803

The ¼ sec. cor. of secs. 25 and 26, monumented with an iron post, 2½" dia., firmly set, projecting 1" above a mound of stone, 1 ft. base, 6" high, with brass cap (properly) mkd. from which the remains of an original bearing tree

A fir, 42" dia., bears S.59°E., 19.1 ft., with a healed blaze.

and a bearing tree mkd. by Brooks

A cedar, 16" dia., bears N.33½°W., 6.9 ft., with a healed blaze.