

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3595)  
-----  
Set a basalt stone 16x10x10", 11" in the ground for cor. of secs. 23, 24, 25, & 26 marked with 2 notches on S & 1 notch on E edges, from which  
A fir, 10" dia., bears N.59½°E., 75 lks., mkd: T25S R2W S24 BT.  
A hemlock, 10" dia., bears S.28°E., 13 lks., mkd: T25S R2W S25 BT.  
A hemlock, 7" dia., bears S.21°W., 57 lks., mkd: T25S R2W S26 BT.  
A hemlock, 18" dia., bears N.28°W., 16 lks., mkd: T25S R2W S23 BT.

Glen McChesney, Weyerhaeuser Co. - 8/1958 - C.S. 53/112-41  
-----  
Found - Orig. stone with notches & with  $\frac{23|24}{26|25}$   
12" scribed hemlock, bears N.61°E., 49.5'  
10" hemlock stub 12' high, bears S.25°E., 38.4'  
10" hemlock scribed, bears S.16°W., 9.3'  
26" scribed hemlock bears N.28°W., 9.6'  
New - 10" hemlock (OBT) bears N.61°E., 49.2' added "W" nail & plate.  
38" hemlock bears S.88°E., 38.5 ft. "W" nail & plate  
18" cedar bears S.14°W., 27.0 ft. "W" nail & plate.  
26" hemlock (OBT) bears N.31°W., 8.9 ft. added "W" nail & plate.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13216)  
-----  
The cor. of secs. 23, 24, 25 & 26, monumented with a basalt stone, 16x10x10", firmly set 4" in the ground, marked with 2 notches on the S & 1 notch on the E edge, from which the orig. BTs:  
A hemlock, 13" dia., bears N.61°E., 75 lks., with scribe mark 2 visible on partly healed blaze. (Rec. calls for a fir, bearing N.59½°E.)  
A hemlock snag, 11" dia., bears S.25°E., 59 lks., with scribe marks 25 BT visible on partly healed blaze. (Rec. bearing & dist., S.28°E., 13 lks.)  
A hemlock, 10" dia., bears S.19°W., 14 lks., with scribe marks T25S R2W on rotted face of unhealed blaze. (Rec. bearing & dist., S.21°W., 57 lks.)  
continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor Secs 23, 24, 25, & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A hemlock, 28" dia., bears N.28°E., 16 lks., with a healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked:

T25S R2W  
S 23 | S 24  
S 26 | S 25  
1962

from which new BTs

A hemlock, 40" dia., bears S.87°E., 61 lks., mkd: T25S R2W S25 BT.

A cedar, 24" dia., bears S.6¼°W., 42 lks., mkd: T25S R2W S26 BT.

Deposit the orig. corner stone alongside the iron post.

BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford, & G. Steven Popken Cadastral Surveyors & Glenn S. Baughman, LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct 1975 - (DCSO recs Vol. 36 Page 15114)

-----  
The cor. of secs. 23, 24, 25, & 26, remonumented by Brooks, in 1962, with an iron post, 2½" dia., firmly set, protruding 4", above ground, with brass cap mkd.

T25S R2W  
S 23 | S 24  
S 26 | S 25  
1962

from which the remaining original bearing trees

A hemlock, 13" dia., bears N.61°E., 75 lks., with scribe mark 2 visible on open blaze.

A hemlock, 13" dia., bears S.19°W., 14 lks., with scribe marks T25S R2W visible on decaying blaze.

A hemlock, 28" dia., bears N.28°W., 16 lks., with healed blaze.

and a bearing tree mkd. by Brooks

A cedar, 25" dia., bears S.6¼°W., 42 lks., with scribe marks T25S R2W S26 BT visible on open blaze.

and a new bearing tree

A hemlock, 8" dia., bears S.59°E., 137 lks., mkd. T25S R2W S25 BT.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor, Group #1979, surveyed 2001/2002- (DCSO rec. Vol. 54 Pages 20907-8)

-----  
The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap (properly) mkd. continued next pg

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor Secs 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees  
A hemlock stump, 18" dia., bears S.25°E., 42.6 ft., with healed blaze. (Record, 38.9 ft.)  
A roothole, bears S.19°W., 9.2 ft., with sawed & decayed hemlock stump pushed over alongside, no marks visible.  
A fallen hemlock, 32" dia., bears N.38°W., 10.5 ft., with no marks visible on partially healed blaze. (Record, N.28°W.)  
and remains of a bearing tree mkd. by Brooks  
A sawed cedar stump, 34" dia., bears S.6½°W., 27.7 ft., with scribe marks BT visible on partially healed blaze.  
and new bearing trees  
A fir, 6" dia., bears N.62¼°E., 32.6 ft., mkd. T25S R2W S24 BT.  
A hemlock, 5" dia., bears S.75°E., 14.2 ft., mkd. T25S R2W S25 BT.  
A hemlock, 7" dia., bears S.11½°W., 32.8 ft., mkd. T25S R2W S26 BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.  
From this point, National Geodetic Survey station "STEAM 1989" bears S.75°20'40"E., 42,789.90 ft. (mean bearing & sea level), monumented with a brass disk set in concrete, buried 8 ins. below surface of parking area, in a monument well, mkd. OREGON PRIMARY GPS STATION STEAM 1989 and a triangle.

---

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 3/30/2022 (Filed 7/21/2022) - C.S. File 67/52-31  
-----  
Found - 3¼" BC (properly mkd) in mound of stone, proj. 7".  
Orig. BT  
Well defined root hole S.19°W., 9.2 ft.  
BT by Brook 1962  
Mostly burnt 2' tall cedar stump S.6½°W., 27.7 ft.  
BTs by Skeesick 201-2002  
Burnt-sawn 15"x2' N.61½°E., 32.7 ft. (rec N.62¼°E., 32.6 ft.) 3½" PK nail top center, blaze visible at 6" dia.  
Burnt-dead 11" Hemlock S.78½°E., 14.0 ft (rec S.75°E., 14.2 ft. PK right side center, partly healed blaze partial scribe visible.  
15" burnt-dead Hemlock S.8°W., 33.1 ft (rec S.11½°W., 32.8 ft) partly healed face burnt away.  
Brass washer in face. PK nail right side center.  
Note - Area burnt 9/2020 Compass decl. 14½°E.  
See sketch in file  
Lat: 43°22'23.60"N Long: 122°53'38.12"W