

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3601)

Set a basalt stone 18x8x6", 12", in the ground for cor. of secs. 1, 2, 11 & 12 marked with 5 notches on & 1 notch on edges, from which,

- A fir, 48" dia. bears N.30°E., 9 lks., mkd: T25S R2W S1 BT
- A cedar, 6" dia., bears S.68°E., 50 lks., mkd: T25S R2W S12 BT.
- A fir, 14" dia., bears S.19½°W., 15 lks., mkd: T25S R2W S11 BT.
- A fir, 36" dia. bears N.24°W., 14 lks. mkd: T25S R2W S2 BT

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13342)

The cor. of secs. 1, 2, 11, & 12, monumented with a basalt stone, 18x8x6", firmly set, marked with 5 notches on the S & 1 notch on the E edges, from which the original bearing trees:

- A fir, 54" dia., bears N.54½°E., 11 lks., blaze healed. (Record: bears N.30°E., 9 lks.)
- A cedar, 10" dia., bears S.61°E., 50 lks., blaze healed. (Record bearing, S.68°E.)
- A fir, 20" dia., bears S.11½°W., 17 lks., blaze healed. (Record: bears S.19½°W., 15 lks.)
- A fir, 40" dia., bears N.13°45'W., 14 lks., blaze healed. (Record bearing, N.24°W.)

At the corner point

Set an iron post, 36" long, 2" diam., 28" in the ground, with brass cap mkd.

T25S	R2W
<u>S 2</u>	<u>S 1</u>
S 11	S 12
1951	

No new accessories established.

Bury the original corner stone alongside the iron post.

Douglas Co. Surveyors Office - Larry E. Monrean - Pete L. Earle - Sept. 21, 1976 - C.S. File 59/24-1

Found - 1951 GLO brass cap properly stamped.

Orig. Corner stone set firmly on Northwest edge of cap. 5 notches on W face, 1 notch on S face.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

48" now 50" Fir stump, bears N.45°E., 7.2 ft. to center, 5.6 ft. to face (orig. 1900, N.30°E., 5.9 ft; Rec. 1951, N.54½°E., 7.3 ft.) Stump has well healed blaze with Weyerhaeuser tag and nail. I do not open for scribing.

A 6" now 21" I.Cedar, bears S.65°E., 33.0 ft. (Rec. 1900, S.68°E. 33.0 ft; Rec. 1951, S.61°E.) Tree has well healed blaze with Weyerhaeuser tag & nail, I do not open blaze.

A 36" now 42" D.Fir, bears N.22°W., 9.2 ft. to center, (Rec. 1900 N.24°W; Rec. 1951, N.13°45'W) Tree has well healed blaze with Weyerhaeuser tag and nail, I do not open blaze.

The SW BT is gone.

New BT - A 16" D. Fir (broken top) bears S.17½°W., 46.3 ft. Tree double blazed & scribed "T25S R2W S11 CS BT"

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2348, Surveyed Aug. 2011 - (DCSO records BLM Plat T25-2W 2012-1 & Vol. 58 Pages 22940-1)

The cor. of secs. 1, 2, 11, and 12, perpetuated by the Douglas County Surveyors Office in 1976, monumented with an iron post, 2" dia., firmly set, projecting 16" above ground, (alongside of which is the original stone, 6x8", firmly set, projecting 12" above ground, with 5 notches on N. edge and 1 notch on W edge) with a brass cap oriented NE (properly) mkd from which the remains of the original bearing trees

A sawed fir stump, 48" dia., bears N.54½°E., 7.3 ft., with a healed blaze.

A cedar, 36" dia., bears S.61°E., 33.0 ft., with a healed blaze.

A fir, 48" dia., bears N.13¾°W., 9.2 ft., with a healed blaze.

and a BT mkd. by the Douglas County Surveyor's Office

A fir, 28" dia., bears S.22°W., 46.6 ft., with a healed blaze.

Add a collar of stone around iron post and incorporate original stone into collar.