

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T24-2

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____


GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2867-68)

 Set post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 2, 35 and 36, marked T24S S36 on NE.; R2W S1 on SE.; T25S S2 on SW.; and S35 on NW. faces, with 5 notches on W. and 1 notch on E. edges, from which
 A Fir 30" dia., bears N.21°E., 18 lks. dist. mkd. T24S R2W S36 BT.
 A Fir 41" dia., bears S.20°E., 69 lks. dist. mkd. T25S R2W S1 BT.
 A Maple 8" dia., bears S.32°W., 15 lks. dist. mkd. T25S R2W S2 BT.
 A Fir 20" dia., bears N.82°W., 20 lks. dist. mkd. T24S R2W S35 BT.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13277)

 "The intermediate corners along this line which were established by McQuinn formerly referred only to T. 24 S., R. 2 W. The purported retracement of the south boundary of sec. 31 and the reported establishment of closing corners on the boundary by Hezekiah Johnson in 1900 **having proved to be fictitious**, the McQuinn corners except for the south ¼ sec. cor. of sec.31 and the south ¼ sec. cor. of sec. 36, are changed in 1963 to corners of maximum control in order to provide a basis for Consent Decree "Civil No. 60-135, Oregon." (Hezekiah Johnson fictitious corner on Page 3602)

Point for the cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. This now becomes the cor. of secs. 1, 2, 35 and 36. Set an iron post 36" long, 2" dia., 28" in the ground with brass cap mkd.



from which bearing trees mkd. in 1963:
 A Fir 35" dia., bears N.56°E., 184 lks. dist. mkd. T24S R2W S36 BT.
 A Pine stump 44" dia., bears S.28°E., 28 lks. dist. mkd. T25S R2W S1 BT.

(Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T24-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Pine stump 42" dia., bears S.23½°W., 46 lks. dist. mkd.
T25S R2W S2 BT.
A Fir 35" dia., bears N.83½°W., 63 lks. dist. mkd. T24S
R2W S35 BT.

David Edwards - 7/21/2014 - C.S. file 65/82-59

Found - 1951 BLM brass cap, Standard BLM brass capped iron
pipe.
35" dia. Fir snag bears N.56°E., 121.4 ft w/healed
blaze.
44" dia. Pine stump bears S.28°E., 18.5 ft.
42" dia. Pine stump bears S.23½°W., 30.4 ft.
The fir N.83¼°W., 41.6 ft is gone.
New - A 10" dia. Fir snag scribed "T25S R2W S1 BT" bears
S.42°E., 4.45 ft.
A 6" dia. Fir scribed "T25S R2W S2 BT" bears
S.60°W., 14.45 ft. 6 ft steel posts are set
N.22°E., 2 ft and S.6½°E., 2 ft.
Compass decl. 15½°E.